

IP66 Mechanism holder and manual frame with italian P40 socket and RJ45 Keystone lodge

REF. KFH131/74



BASIC INFORMATION

DESCRIPTION

Simon completely renews its range of waterproof floor boxes for indoor and outdoor environments. This is a framework for manual closing mechanisms with an Italian P40 electrical base and accommodation for a Keystone RJ45 connector. In combination with its base, it will allow installation in technical flooring or pavement. The product design, combined with its manufacture from stainless steel, achieves a robust, solid, and secure installation as it withstands a water jet of 1 kg/cm² from any direction, reaching an IP66 protection rating when the lid is closed. It also supports a maximum load of 1500 kg and has an IK08 impact resistance. It maintains an optimal bending radius of cabling in high-category voice and data connections. Available is our accessory for plug connection with a closed lid, allowing us to keep our connections active with an IP54 (see reference KFA1001), the possibility to level our box in case of having an irregular floor (see reference KFA1003), or the ability to concatenate more than one box (see reference KFA1002).

FINISH

Black

COMPATIBILITY

K45 Solutions

MATERIAL

Polycarbonate

ETIM CLASS

EC000024

REMARKS

To complete the installation of the product, it must be combined with a tray for the IP66 waterproof floor box.

TECHNICAL INFORMATION

FORMAT

Italian

IP RATING

IP66

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

IK CLASSIFICATION

08

KIT AVAILABILITY

Yes

CURRENT (A)

16 A

MAXIMUM LOAD (KG)

1500 Kg - Closed box | 250 Kg - Open box

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS

Only with tool

EXTINGUISHING (°C)

+650 °C (according to standard
IEC 60670)

REMOVAL OF THE SOCKET

Only with tool

NUMBER OF COVER OPENING POSITIONS

1

REMOVAL OF THE FRAME

Only with tool

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2011/65/UE RoHS + post. mod. | EN 60670-23:2008 | EN IEC 63000:2018 | IEC 60884-1 Ed 3.2 | CEI 23-50 V4

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053333037

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053333037

PACKAGING VOLUME

1837680

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

114

PACKAGING GROSS WEIGHT

0.46

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

124

PACKAGING NET WEIGHT

0.382

UNITARY PACKAGING GROSS
WEIGHT

0

PACKAGING LENGTH

130

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

0.382