Flat voice and data plate with dust cover for 1 element with 2 RJ45 category 6 FTP graphite Simon 500 Cima

REF. **50003089-038**



BASIC INFORMATION

DESCRIPTION

Flat base plate for voice and data in graphite colour of the Simon 500 Cima range with a dust cover with 1 element and 2 RJ45 category 6 FTP of the signature Keystone I, II, ATT ® / Avaya ®. Its installation is very simple and no vas to need any type of adapter for fastening in enclosures horizontal or vertical, as this plate includes the clips required. Designed according to the regulation TIA 568 C. 2, the Simon 500 Cima graphite plate has been manufactured with the best materials and safest: Metal components with self-extinguishing, halogen-free thermoplastic insulation. Thanks to these materials, it is not propagate the fire, in case of fire, and if had smoke, the levels toxic does not would be high. It measures 50 x 50 x 45,4 mm and can be installed perfectly in places where the temperature is located between the -5 and 60 ° C, approximately.

FINISH

Graphite

COMPATIBILITY

Simon 500 Cima enclosures

PACKAGING CONTENTS

Flat voice and data plate with dust cover, 2 RJ45 category 6 FTP and installation manual

ETIM CLASS

EC000018

REMARKS

The plate is snap-fitted for mounting in vertical and horizontal enclosures without the need for an adaptor.

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

CABLE SECTION ADMITTED (MM)
22-26 AWG wiring

RJ45 CONNECTION
Without insertion tool

CONNECTOR CHARACTERISTICS
category 6 FTP

NUMBER OF CONNECTORS
2

RJ45 CONNECTORS
Included in voice and data plate

MAX TEMP DURING CONSTRUCTION WORK (°C)
+60 °C

DUST PROTECTION
Yes

FORMAT
RJ45

IP RATING
IP20

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 to 60 °C

NUMBER OF MODULES
1

PLATE TYPE
Flat

RAL
7021

RJ45 ADAPTOR MODULE
Included in voice and data plate

SNAP-FIT RJ45 PLATES
Keystone I, II, ATT®/Avaya®

SNAP-FIT TYPE
Keystone I, II, ATT®/Avaya®

VERSION
Single

INSTALLATION AND MAINTENANCE

REMOVAL OF CONNECTOR

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX
Specific Simon 500 Cima

INSTALLATION DIRECTION
Vertical, corresponding with the direction of the mechanisms

INSTALLATION TYPE
Fixing by direct snap-fit, no tools needed.

REMOVAL OF THE PLATE
Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
0.056

PRODUCT NET WEIGHT
0.056

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053097892

UNITS CONTAINED PACKAGING
20

PACKAGING HEIGHT
80

PACKAGING WIDTH
224

PACKAGING LENGTH
290

PACKAGING MEASUREMENT UNIT
MMT


PACKAGING VOLUME
0.052

PACKAGING VOLUME UNIT
HLT

PACKAGING GROSS WEIGHT
0

PACKAGING NET WEIGHT
1.12

PACKAGING WEIGHT UNIT
KGM


50
50
5
11