

Flat voice and data plate without dust cover for 1 element with 1 RJ45 category 6 UTP white Simon 500 Cima

REF. 50002185-030



BASIC INFORMATION

DESCRIPTION

This is a voice and data plate in flat format with dust shutter of 1 element for 1 RJ45 connector category 6 UTP. The article is white in colour, measures 50x50x32,5 mm and is part of the Simon 500 Cima series, a collection whose mechanisms have been designed to facilitate the workplace solutions in any environment. It is in compliance with the current regulation and consists of metal components with halogen-free in self-extinguishing halogen-free thermoplastic material, a 100% safe in case of fire, as it avoids the fire is propagate and guarantees the low toxicity in the presence of smoke. The product comes with clips for its proper fastening in vertical and horizontal enclosures. There is no need adapter. In terms of the cleaning of the plate, the manufacturer recommends using a soft and dry cloth and to avoid, as far as possible, abrasive cleaners containing chlorine.

FINISH

White

PACKAGING CONTENTS

Flat voice and data plate without dust cover, RJ45 connector category 6 UTP and installation manual

ETIM CLASS

EC000018

COMPATIBILITY

Simon 500 Cima enclosures

REMARKS

The plate is snap-fitted for mounting in vertical and horizontal enclosures without the need for an adaptor.

TECHNICAL INFORMATION

AVAILABLE MARKET CE	DUST PROTECTION No	NUMBER OF MODULES 1
CABLE SECTION ADMITTED (MM) 22-26 AWG wiring	DUST SHUTTER No	PLATE TYPE Flat
AVAILABLE IN Plate for 1 and 2 RJ45	FORMAT RJ45	RAL 9003
RJ45 CONNECTION With insertion tool	IP RATING IP20	RJ45 ADAPTOR MODULE Included in voice and data plate
CONNECTOR CHARACTERISTICS category 6 UTP	KIT AVAILABILITY No	SNAP-FIT RJ45 PLATES Keystone I, II, ATT®/Avaya®
NUMBER OF CONNECTORS 1	MAINTENANCE Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.	SNAP-FIT TYPE Keystone I, II, ATT®/Avaya®
RJ45 CONNECTORS Included in voice and data plate	TEMPERATURE RANGE DURING INSTALLATION (°C) -5 to 60 °C	VERSION Single
MAX TEMP DURING CONSTRUCTION WORK (°C) +60 °C		

INSTALLATION AND MAINTENANCE

REMOVAL OF CONNECTOR	INSTALLATION DIRECTION Vertical, corresponding with the direction of the mechanisms	INSTALLATION TYPE Fixing by direct snap-fit, no tools needed.
INSTALLABLE IN FLUSH MOUNT JUNCTION BOX Specific Simon 500 Cima		REMOVAL OF THE PLATE Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053098127

PACKAGING VOLUME

0.052

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

20

PACKAGING VOLUME UNIT

HLT

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

80

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING GROSS
WEIGHT

0.06

PACKAGING WIDTH

224

PACKAGING NET WEIGHT

1.2

PRODUCT NET WEIGHT

0.06

PACKAGING LENGTH

290

PACKAGING WEIGHT UNIT

KGM

