

Adjustable 3-phase rail Surface-mounted 2 m Black

REF. 99921238-039



BASIC INFORMATION

APPLICATION

Domestic,Office,Retail,Contract

PACKAGING CONTENTS

1 Unit

TECHNICAL INFORMATION

OPERATING TEMPERATURE RANGE (°C)

0 - 35 °C

RAL

9005

CONTROL

1-10 V

DIRECTIONAL

No

DRIVER INCLUDED

No

ENERGY EFFICIENCY

A+

INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Flush-mounted

INSTALLATION TYPE

Surface-mounted

REGULATIONS

EAC MARKED

No

ECORRAE MARKED

No

WARRANTY

3 years

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8436547037247

PACKAGING VOLUME

0

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

0

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING GROSS WEIGHT

0

PACKAGING WIDTH

0

PACKAGING NET WEIGHT

2.68

PRODUCT NET WEIGHT

2.68

PACKAGING LENGTH

0

PACKAGING WEIGHT UNIT

KGM