

LedFlex 810.62 2700 K IP65 240 LED/m

REF. 81062100-982



BASIC INFORMATION

APPLICATION

General lighting, Indoor decorative lighting

PACKAGING CONTENTS

1 unit (5m)

ETIM CLASS

EC002706

TECHNICAL INFORMATION

IP RATING

IP65

DRIVER INCLUDED

No

LUMENS/W

8700 lm/70W

OPERATING TEMPERATURE RANGE (°C)

-20 - 40 °C

L70 (°C)

30,000 h

OPTICS

General

COLOR TEMPERATURE (K)

2700 K

LIGHT BEAM APERTURE ANGLE (°)

120°

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

CONTROL

PWM

LIGHTING EFFICIENCY (LM/W)

124,3 lm/W

POWER (W)

70 W

CRI

80

LUMENS (LM)

8700 lm

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

Hardware

REGULATIONS

WARRANTY

3 years

LOGISTICS INFORMATION

UNITARY EAN CODE 8421053203149	UNITARY PACKAGING WEIGHT UNIT KGM	PACKAGING MEASUREMENT UNIT MMT
UNITARY PACKAGING HEIGHT 0	PACKAGING EAN 8421053203149	PACKAGING VOLUME 1200
UNITARY PACKAGING WIDTH 0	UNITS CONTAINED PACKAGING 1	PACKAGING VOLUME UNIT MMQ
UNITARY PACKAGING LENGTH 0	PACKAGING HEIGHT 2	PACKAGING GROSS WEIGHT 450.2
UNITARY PACKAGING VOLUME 0	PACKAGING WIDTH 24	PACKAGING NET WEIGHT 0.45
UNITARY PACKAGING GROSS WEIGHT 0.45	PACKAGING LENGTH 25	PACKAGING WEIGHT UNIT GRM
PRODUCT NET WEIGHT 0.45		