Charger USB type A+C port 18W QuickCharge white Simon K45

REF. **K126F/9**



BASIC INFORMATION

FINISH
White

MATERIAL
Thermoplastic

COMPATIBILITY
K45 Solutions. 500 Cima solutions through adapter 50012088-030.

ETIM CLASS
EC002949

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

NUMBER OF CONNECTORS
2

CONNECTOR TYPE
USB A + USB C

NUMBER OF CONTACTS
2

FORMAT
USB A + USB C

IP RATING
IP20

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

NOMINAL VOLTAGE (V~)
230 V~

PLATE TYPE
Flat

POWER SUPPLY (V~)
230 V~

RAL
9003

RECESS DIMENSION (MM)
40

USB CHARACTERISTICS
QC 18W

QUICK CHARGE USB
Yes

NUMBER OF WIRES
2

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)
10

REMOVAL OF CONNECTOR
Only with tool

EXTINGUISHING (°C)
+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-10-2)

INSTALLATION DIRECTION
Horizontal, Vertical

TYPE OF TERMINAL CONNECTION - FUNCTION 1
Screw

TYPE OF TERMINAL CONNECTION - FUNCTION 2
Screw

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2011/65/UE RoHS + post. mod. | Dir. 2014/30/UE EMC | Dir. 2009/125/EC ErP (Reg. UE 2019/1782) | EN IEC 61000-3-2:2019 + A1:2021 + A2:2024 | EN 50563:2011 + A1:2013 | EN 61000-3-3:2013 + A1:2019 + A2:2021 EN IEC 62368-1:2020 + A11:2020 | EN 50563:2011 + A1:2013 | EN IEC 61000-6-1:2019 | EN IEC 63000:2018 | EN IEC 61000-6-3:2021

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053313428

UNITARY PACKAGING HEIGHT
55

UNITARY PACKAGING WIDTH
65

UNITARY PACKAGING LENGTH
65

UNITARY PACKAGING MEASUREMENT UNIT
MMT

UNITARY PACKAGING VOLUME
232375

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.079

PRODUCT NET WEIGHT
0.079

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053313428

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
55

PACKAGING WIDTH
65

PACKAGING LENGTH
65

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
232375

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.82

PACKAGING NET WEIGHT
0.079

PACKAGING WEIGHT UNIT
KGM