

Spotlight 880.33 industrial 4000 K ASYM

REF. 88033038-274



BASIC INFORMATION

APPLICATION

Accent lighting, General lighting

PACKAGING CONTENTS

1 unit

ETIM CLASS

EC001744

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

CONTROL

On/Off

LIGHTING EFFICIENCY (LM/W)

121,3 lm/W

IK CLASSIFICATION

08

CRI

70

LUMENS (LM)

18200 lm

IP RATING

IP65

DIRECTIONAL

Yes

LUMENS/W

18200lm/ 150W

OPERATING TEMPERATURE RANGE (°C)

40 °C maximum

DRIVER INCLUDED

Yes

OPTICS

Asymmetric

POWER SUPPLY (V~)

100/240 V~

L70 (°C)

100,000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

COLOR TEMPERATURE (K)

4000 K

L90 (°C)

30,000 h at 25 °C

POWER (W)

150 W

COLOR TYPE

NW

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

Surface (with bracket)

REGULATIONS

WARRANTY

5 years

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053205532

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

7

PRODUCT NET WEIGHT

5.316

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053205532

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

130

PACKAGING WIDTH

515

PACKAGING LENGTH

435

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

29123250

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

7

PACKAGING NET WEIGHT

5.316

PACKAGING WEIGHT UNIT

KGM