

Voice and data flat plate with dust cover for 1 element for 1 Panduit® RJ45 connector white Simon K45

REF. KA69/9



BASIC INFORMATION

DESCRIPTION

Plate for data and voice plate of the series Simon K45 white in colour, it is a plate with dust cover with 1 element and that is used for 1 RJ45 connector of the signature Panduit ®. It is manufactured according to the regulation UNE-EN 60670-1: 2006 in white thermoplastic material, which is a perfect to prevent the propagation of the fire and also the high levels of toxicity if producing a smoke. It measures 45 x 45 mm and 8.5 mm depth and is a plate suitable both for surface and flush mounting in rooms with a temperature between -5 and the most of 60 ° C You can combine in vertical enclosures and to keep it in perfect condition just need a soft, dry cloth and nothing cloths and / or detergents cleaners that have chlorine in its formulation, since the plate can be damaged and thus to prevent their correct operation.

FINISH

White

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-030)

PACKAGING CONTENTS

Flat voice and data plate with dust cover

ETIM CLASS

EC000018

REMARKS

When combining the voice and data plate in vertical housings (mini columns, columns, Teleblock, channels, mechanism holders, etc.) you must use the 90° positioner (ref. K66) to guide the plate into a vertical position.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST SHUTTER

Yes

NUMBER OF MODULES

Four

AVAILABLE IN

Plate for 1 and 2 RJ45 connectors

FORMAT

RJ45

PLATE TYPE

Flat

COMPATIBLE WITH CONNECTORS

Panduit® Mini-Com Series.

IP RATING

IP20

RAL

9003

RJ45 CONNECTORS

Not included in voice and data plate

KIT AVAILABILITY

No

RJ45 ADAPTOR MODULE

Included in voice and data plate

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT RJ45 PLATES

Panduit® RJ45 connectors

SNAP-FIT TYPE

Panduit® RJ45 connectors

DUST PROTECTION

Yes

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

VERSION

Single

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-030)

INSTALLATION DIRECTION

Vertical according to the direction of the mechanisms

INSTALLATION TYPE

Suitable for surface and flush mounting

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.007

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

544320

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8426436045071

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

0.3

UNITS CONTAINED PACKAGING

20

PACKAGING GROSS WEIGHT

0.14

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING HEIGHT

72

PACKAGING NET WEIGHT

0.14

UNITARY PACKAGING GROSS WEIGHT

0.007

PACKAGING WIDTH

72

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

105