

Downlight 706.21 Flush mount WW Flood 1-10V White

REF. 70621130-383



BASIC INFORMATION

DESCRIPTION

The series Simon 706 stands out for the ease with which they can instarse products and accessories included in its wide catalogue. In this range, we can take the Downlight 706.21 WW Flood and optical with electrical control of the 1-10V type, an element suitable to be flush mounted, which is the best ally for individuals and professionals to have the conditions of the desired indoor lighting for each situation and space in all types of buildings. Its main features are: Dimensions of 110x82 () mm, detailed frequency of 50 / 60 Hz and power 100-240. Also, the weight of the luminaire is 0.3 kg and has lumens watt of 900 lm / 15 W University campuses and residential centres, for the development of activities sports and leisure or hotels and holiday resorts are some of the spaces that already illuminate crossing its interior installations with this spotlight that stands out for its low price.

APPLICATION

Ambient lighting

PACKAGING CONTENTS

1 unit

ETIM CLASS

EC001744

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

DRIVER INCLUDED

Yes

LUMENS/W

900 lm/15W

IP RATING

IP44

ELECTRICAL CLASS

Type 2

OPTICS

Flood

OPERATING TEMPERATURE RANGE (°C)

40 °C maximum

INTEGRATED POWER SUPPLY

No

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

POWER SUPPLY (V~)

100/240 V~

L70 (°C)

30,000 h at 25 °C

POWER (W)

15 W

COLOR TEMPERATURE (K)

3100 K

COLOR TYPE

WW

POWER SUPPLY DIMENSIONS (MM)

45x141x26 mm

CONTROL

1-10 V

LIGHTING EFFICIENCY (LM/W)

60 lm/W

SERVICE LIFE

30.000 h

CRI

80

LUMENS (LM)

900 lm

CHROMATICS CRI ICONS

CRI
80

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

180

INSTALLATION TYPE

Flush mount

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Screw

REGULATIONS

WARRANTY

3 years 30,000 h

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0.506

PRODUCT NET WEIGHT

0.506

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053122198

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

135

PACKAGING WIDTH

145

PACKAGING LENGTH

155

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

3.034

PACKAGING VOLUME UNIT

DMQ

PACKAGING GROSS WEIGHT

0.506

PACKAGING NET WEIGHT

0.506

PACKAGING WEIGHT UNIT

KGM