Hinged cover for adjustable floor box or service cover in concrete or raised floor for 8 elements graphite Simon 500 Cima

REF. **RSF004/14**



BASIC INFORMATION

DESCRIPTION

This hinged cover for adjustable floor box or inspection cover is valid both for concrete floor and raised floor. For 8 elements and finished in graphite, of the Simon 500 Cima series, a collection that allows the maximum workplace solutions, in terms of functionality and speed, in the different work stations that concreto of installations as it. This product has dimensions of 160 x 256 x 15 millimetres. The adjustable floor boxes include a hinged cover itself. In the event of breakage or loss, which has the same, you can request a replacement. Also, this cover is manufactured in quality metal components with thermoplastic insulation and halogen-free, which guarantees the total security of users (avoiding which, if a fire is spread the flame and reducing the toxicity emitted). To clean, just have to use a cloth and slide slightly. Always dry and, above all, avoiding any cleaner with abrasive components such as chlorine.

FINISH

Graphite

PACKAGING CONTENTS

Hinged cover

MATERIAL

Plastic

ETIM CLASS

EC001903

REMARKS

The adjustable floor boxes include the hinged cover. Only necessary to order it as a replacement part in the event of breakage or loss.

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

PROTECTION AGAINST DIRECT ACCESS OF CONTACTS
No

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS
Yes, thanks to the inclusion of protective foam

AVAILABLE IN
2, 4, 6, 8 and 12 elements

DIELECTRIC STRENGTH
No holes or contours, with 2000V at 50 Hz for 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)
+90 °C

HEAT RESISTANCE (°C)
+125°C (according rule IEC 60695-10-2)

INSULATION RESISTANCE (V-MΩ)
>5 MOhms at 500V

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 to 60 °C

NUMBER OF MODULES
8 modules

RAL
7021

VERSION
8 elements

INSTALLATION AND MAINTENANCE

TYPE OF FASTENING
Via coupling pin supplied on the cover

INSTALLATION DIRECTION
Horizontal and vertical, in accordance with the installation of the floor box or service cover

INSTALLATION TYPE
In raised or concrete floor with adjustable floor boxes or service covers

REGULATIONS

REGULATIONS
UNE-EN 60.670-23

LOGISTICS INFORMATION

UNITARY EAN CODE
8426436056244

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING MEASUREMENT UNIT
MMT

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.913

PRODUCT NET WEIGHT
0.913

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436056244

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
20

PACKAGING WIDTH
350

PACKAGING LENGTH
250

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
2.625

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0

PACKAGING NET WEIGHT
0.913

PACKAGING WEIGHT UNIT
KGM