

PD-12 HF+LUX BT Mesh recessed box BT-Slave white IP20

REF. 89214623-230



BASIC INFORMATION

DESCRIPTION

Presence and brightness detector for flush mounting HF. The recommended installation height is 2.8 m, with a maximum height of 4 m. It has a detection angle of 360° and an opening angle of 140°. The tangential detection range is 12 m and the radial detection range is 12 m.

The brightness regulation range is 2 - 2000 lux. The configuration of the detector is done through a Bluetooth application.

Possibility of interconnection between sensors via Bluetooth. The control protocol is Bluetooth slave. The power supply voltage is 220 - 240 VAC. The operating temperature of the detector is: -20 - 50 °C. White finish, protection grade IP 20, and dimensions: 103 x 103 x 61 mm.

5-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

ETIM CLASS

EC000133

COMPATIBILITY

Simon Sensor Pro

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

MAXIMUM POWER (W)

2000

RAL

9003

IP RATING

IP20

POWER SUPPLY (V~)

220/240 V~

CONTROL

Bluetooth Slave

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

2.5

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053357897

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.251

PRODUCT NET WEIGHT

0.142

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053357897

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

161

PACKAGING WIDTH

101

PACKAGING LENGTH

143

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

2325323

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.251

PACKAGING NET WEIGHT

0.142

PACKAGING WEIGHT UNIT

KGM