Projector 889 200W 5500K

REF. **88935038-885**



BASIC INFORMATION

DESCRIPTION

Outdoors LED projector for shop window and facade lighting, robust, adjustable, and designed for high performance in commercial applications. Available in different power levels, the outdoor projector 889 allows you to select the appropriate model based on the mounting height, the surface to be illuminated, and the desired impact level. Installation type: Surface. Optics: 110. Color temperature: 5500K. Power: 200W. Lumens: 18000lm. Efficiency: 90lm/w. Protection grade IP: IP65. Power supply: 220-240 V. 50/60 Hz. Dimensions: 406 mm x 333 mm x 47 mm.

APPLICATION

Wall lighting,Industrial lighting,Commercial areas

TECHNICAL INFORMATION

FREQUENCY
50 - 60 Hz

IK CLASSIFICATION
05

IP RATING
IP65

OPERATING TEMPERATURE RANGE (°C)
-25...+50

POWER SUPPLY (V~)
220/240 V~

CONTROL
On/Off

LIGHTING EFFICIENCY (LM/W)
90 lm/W

LUMENS (LM)
18000 lm

OPTICS
Symmetric

POWER (W)
200 W

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE
Surface / Wall

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053440469

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
2.394

PRODUCT NET WEIGHT
2.29

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053440469

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
350

PACKAGING WIDTH
125

PACKAGING LENGTH
430

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
18812500

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
4.788

PACKAGING NET WEIGHT
2.29

PACKAGING WEIGHT UNIT
KGM