

Spotlight 615 rail 4000 K Spot white

REF. 61500030-284



BASIC INFORMATION

APPLICATION

Accent lighting

PACKAGING CONTENTS

1 unit

ETIM CLASS

EC001744

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

CRI

80

LIGHTING EFFICIENCY (LM/W)

95,7 lm/W

IP RATING

IP20

DIRECTIONAL

Yes

LUMENS (LM)

2200 lm

OPERATING TEMPERATURE RANGE (°C)

35 °C maximum

DRIVER INCLUDED

Yes

LUMENS/W

2200lm/ 23W

POWER SUPPLY (V~)

230 V~

L70 (°C)

100,000 h at 25 °C

OPTICS

Spot

COLOR TEMPERATURE (K)

4000 K

L90 (°C)

50,000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

CONTROL

On/Off


COLOR TYPE

NW

POWER (W)

23 W

CHROMATICS CRI ICONS



INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

3-phase adjustable rail

REGULATIONS

WARRANTY

5 years

LOGISTICS INFORMATION

UNITARY EAN CODE 8421053198575	UNITARY PACKAGING WEIGHT UNIT KGM	PACKAGING MEASUREMENT UNIT MMT
UNITARY PACKAGING HEIGHT 0	PACKAGING EAN 8421053198575	PACKAGING VOLUME 4400928
UNITARY PACKAGING WIDTH 0	UNITS CONTAINED PACKAGING 1	PACKAGING VOLUME UNIT MMQ
UNITARY PACKAGING LENGTH 0	PACKAGING HEIGHT 84	PACKAGING GROSS WEIGHT 0.846
UNITARY PACKAGING VOLUME 0	PACKAGING WIDTH 177	PACKAGING NET WEIGHT 0.635
UNITARY PACKAGING GROSS WEIGHT 0.846	PACKAGING LENGTH 296	PACKAGING WEIGHT UNIT KGM
PRODUCT NET WEIGHT 0.635		