

## Downlight 706.21 Flush mount NW Wide Flood 1-10V White

REF. 70621130-484



### BASIC INFORMATION

#### DESCRIPTION

If you are looking for a sustainable lighting, durable and with a design that adapts to each space, the Downlight 706.21 circular of the collection Simon for indoor lighting, it is the ideal decision. With finishes in intense white tone and optics WIDE FLOOD photometric distribution, you will obtain a beam of light that abarque angles widest, with a minimalist design and protocol for the cabinet amplitude dimming 1-10 V light for greater versatility and functionality of lighting. It has a light tone of a white neutral NW, colour temperature of 3900 K, performance 950 lm, and total luminaire consumption of 15 W It of a power of 100-240 Volt and 50-60 Hertz rate, has a service life of 30,000 hours at 25 ° C, being able to reach a maximum temperature of 40 °C. Its installation, recessed, prepared for false ceiling and plastered, it has a dimension of 82 mm diameter x 110 mm depth, which ensures integration of the set in a reduced space.

#### APPLICATION

Ambient lighting

#### PACKAGING CONTENTS

1 unit

#### ETIM CLASS

EC001744

## TECHNICAL INFORMATION

### FREQUENCY

50 - 60 Hz

### DRIVER INCLUDED

Yes

### LUMENS/W

950 lm/15W

### IP RATING

IP44

### ELECTRICAL CLASS

Type 2

### OPTICS

Wide Flood

### OPERATING TEMPERATURE RANGE (°C)

40 °C maximum

### INTEGRATED POWER SUPPLY

No

### PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

### POWER SUPPLY (V~)

100/240 V~

### L70 (°C)

30,000 h at 25 °C

### POWER (W)

15 W

### COLOR TEMPERATURE (K)

3900 K

### COLOR TYPE

NW

### POWER SUPPLY DIMENSIONS (MM)

45x141x26 mm

### CONTROL

1-10 V

### LIGHTING EFFICIENCY (LM/W)

64 lm/W

### SERVICE LIFE

30.000 h

### CRI

80

### LUMENS (LM)

950 lm

### CHROMATICS CRI ICONS

CRI  
80

## INSTALLATION AND MAINTENANCE

### MINIMUM INSTALLATION HEIGHT

180

### INSTALLATION TYPE

Flush mount

### TYPE OF TERMINAL CONNECTION - FUNCTION 1

Screw

## REGULATIONS

### WARRANTY

3 years 30,000 h

## LOGISTICS INFORMATION

### UNITARY PACKAGING HEIGHT

0

### UNITARY PACKAGING WIDTH

0

### UNITARY PACKAGING LENGTH

0

### UNITARY PACKAGING VOLUME

0

### UNITARY PACKAGING GROSS WEIGHT

0.506

### PRODUCT NET WEIGHT

0.506

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING EAN

8421053122242

### UNITS CONTAINED PACKAGING

1

### PACKAGING HEIGHT

135

### PACKAGING WIDTH

145

### PACKAGING LENGTH

155

### PACKAGING MEASUREMENT UNIT

MMT

### PACKAGING VOLUME

3.034

### PACKAGING VOLUME UNIT

DMQ

### PACKAGING GROSS WEIGHT

0.506

### PACKAGING NET WEIGHT

0.506

### PACKAGING WEIGHT UNIT

KGM