

# Extension 0.5 metres for aluminium column with 2 sides oval Simon K45

REF. ALK72P05/8



## BASIC INFORMATION

### DESCRIPTION

Model of element for Pole for fastening to the floor reference ALK72P05 / 8, It is part of the range of products and components of the series Simon professional 500 Cima, suitable for different environments and installations work Professionals and domesticas. It is an extension, 0.5 Meters for pole for fastening to the floor of 2 sides oval Simon K45, with the maximum Guarantees of solidity and versatile for different systems for fastening. Manufactured in aluminium material, Available finishes in colour and tone metal. Measures 500 x 80 x 110 mm, suitable For elements of different kinds of surfaces and environments. Work professionals.

### FINISH

Metal

### COMPATIBILITY

Simon K45 functions

### ETIM CLASS

EC000795

### MATERIAL

Aluminium

### PACKAGING CONTENTS

Column extension, front cover, connecting pins and screws

### REMARKS

To ensure the robustness of the unit, it is only possible to combine one extension per column

## TECHNICAL INFORMATION

### AVAILABLE MARKET

CE

### AVAILABLE IN

2-sided (square and oval) and 4-sided

### DIELECTRIC STRENGTH

Without perforation or contournement with 2000 V at 50H during 1 minute

### MAX TEMP DURING CONSTRUCTION WORK (°C)

+120° C

### EARTHING RESISTANCE

< 0.05 ?

### ELECTRICAL PROPERTIES

With electrical continuity

### ELECTROMAGNETIC IMMUNITY FOR VDM WIRING

Separation by means of the compartments of the extension itself to eliminate any possible electromagnetic interference and transmission errors between the electric cables and Voice, Data and Multimedia.

### HEAT RESISTANCE (°C)

+650°C (according rule IEC 60695-10-2)

### INSULATION RESISTANCE (V-MΩ)

5 MOhms at 500 V.

### IP RATING

IP4X

### KIT AVAILABILITY

No

### MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### TEMPERATURE RANGE DURING INSTALLATION (°C)

-25 a 120° C

### VERSION

2-sided (Oval)

## INSTALLATION AND MAINTENANCE

### REMOVAL OF COMPONENTS

Only with tool

### REMOVAL OF COVER

Only with tool

### TYPE OF FASTENING

Using connecting pins

### INSTALLATION DIRECTION

Vertical

## REGULATIONS

### REGULATIONS

UNE-EN 50.085-2-4:2006

## LOGISTICS INFORMATION

### UNITARY EAN CODE

8426436050549

### PRODUCT NET WEIGHT

1.5

### PACKAGING MEASUREMENT UNIT

MMT

### UNITARY PACKAGING HEIGHT

0

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING VOLUME

5832000

### UNITARY PACKAGING WIDTH

0

### PACKAGING EAN

8426436050549

### PACKAGING VOLUME UNIT

MMQ

### UNITARY PACKAGING LENGTH

0

### UNITS CONTAINED PACKAGING

1

### PACKAGING GROSS WEIGHT

1.5

### UNITARY PACKAGING VOLUME

0

### PACKAGING HEIGHT

90

### PACKAGING NET WEIGHT

1.5

### UNITARY PACKAGING VOLUME UNIT

MMQ

### PACKAGING WIDTH

120

### PACKAGING WEIGHT UNIT

KGM

### UNITARY PACKAGING GROSS WEIGHT

1.5

### PACKAGING LENGTH

540