

## Module Downlight LED Simon 704 2700K WF Negro

REF. 70400038-482



### BASIC INFORMATION

#### APPLICATION

Accent lighting, General lighting

#### ETIM CLASS

EC000996

## TECHNICAL INFORMATION

### FREQUENCY

50 - 60 Hz

### COLOR TEMPERATURE (K)

2700K

### LIGHTING EFFICIENCY (LM/W)

84 lm/W

### IP RATING

IP20

### CONTROL

On/Off

### LUMENS (LM)

1015 lm

### OPERATING TEMPERATURE RANGE (°C)

-15 to 35°C

### CRI

80

### LUMENS/W

1015 lm/12W

### POWER SUPPLY (V~)

220/240 V~

### LIGHT BEAM APERTURE ANGLE (°)

40°

### OPTICS

Wide Flood

### SERVICE LIFE

30.000 h

### CHROMATICS CRI ICONS

CRI  
80

## REGULATIONS

### WARRANTY

3 years 30.000 h

## LOGISTICS INFORMATION

### UNITARY EAN CODE

8421053225509

### UNITARY PACKAGING HEIGHT

115

### UNITARY PACKAGING WIDTH

85

### UNITARY PACKAGING LENGTH

118

### UNITARY PACKAGING MEASUREMENT UNIT

MMT

### UNITARY PACKAGING VOLUME

1.153

### UNITARY PACKAGING VOLUME UNIT

DMQ

### UNITARY PACKAGING GROSS WEIGHT

0.274

### PRODUCT NET WEIGHT

0.23

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING EAN

8421053225509

### UNITS CONTAINED PACKAGING

1

### PACKAGING HEIGHT

115

### PACKAGING WIDTH

85

### PACKAGING LENGTH

118

### PACKAGING MEASUREMENT UNIT

MMT

### PACKAGING VOLUME

1153450

### PACKAGING VOLUME UNIT

MMQ

### PACKAGING GROSS WEIGHT

0.274

### PACKAGING NET WEIGHT

0.23

### PACKAGING WEIGHT UNIT

KGM