

**2-way switch 16AX 250V~ with fast terminal connection system ivory Simon 27 Play**

REF. 27211-62



## BASIC INFORMATION

### DESCRIPTION

The tilting 2-way switch for 1 element, 2 modules of the Simon 27 Play collection, brings to any space the perfect balance between design and innovation. With finishes in a stylish ivory colour, its sober lines and clean ensures integration of the set in environments with minimalist notes functional. Made of metal materials with halogen-free thermoplastic and a thermoset trim, it protects the room in case of fire, to prevent the flame spread and toxicity by smoke. With a size of 45 x 45 mm, supports a cable section of up to 2.5 mm and stripping of 11 mm, and is designed for an installation both recessed and surface-mounted, making the adapting the set to the specific needs of each space and reducing the time of assembly, thanks to its quick terminal connection. It has a power supply is compatible with a voltage of 250 Volt and a maximum load of 16 AX.

### FINISH

Ivory

### COMPATIBILITY

Simon 27 Play, Simon 27 Neos, Simon 27 Scudo, Simon 27, Simon 27 Centralisations and Simon 44 Aqua frames

### PACKAGING CONTENTS

Mechanism with rocker

### ETIM CLASS

EC001590

### REMARKS

Possibility of substituting the finish of the rocker supplied with a different one. 7 additional finishes available.

## TECHNICAL INFORMATION

### AVAILABLE MARKET

CE

### CURRENT (A)

16 AX

### OPERATING TEMPERATURE

RANGE (°C)

5 - 40 °C

### CABLE SECTION ADMITTED (MM)

From 1,5 to 2,5 mm

### IP RATING

IP21

### STORAGE TEMPERATURE RANGE

(°C)

-25 - 50 °C

### NUMBER OF POSSIBLE ELEMENTS

1 element

### MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### VERSION

Single

### INDICATOR FUNCTION

No

### TYPE OF MECHANISM

Pivoting

### VOLTAGE (V~)

250 V~

## INSTALLATION AND MAINTENANCE

### CABLE STRIPPING NECESSARY (MM)

11

### CLAW

Simon 27

### INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, American and  
Centralisations

### INSTALLATION DIRECTION

Horizontal, Vertical

### INSTALLATION TYPE

Suitable for surface and flush  
mounting

### TYPE OF TERMINAL CONNECTION - FUNCTION 1

Fast

## REGULATIONS

### REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2011/65/UE RoHS + post. mod. | EN 60669-1:2018 | EN IEC 63000:2018

## LOGISTICS INFORMATION

UNITARY EAN CODE 8421053251867	UNITARY PACKAGING GROSS WEIGHT 0.043	PACKAGING LENGTH 220
UNITARY PACKAGING HEIGHT 0	PRODUCT NET WEIGHT 0.043	PACKAGING MEASUREMENT UNIT MMT
UNITARY PACKAGING WIDTH 0	UNITARY PACKAGING WEIGHT UNIT KGM	PACKAGING VOLUME 1201200
UNITARY PACKAGING LENGTH 0	PACKAGING EAN 8421053035665	PACKAGING VOLUME UNIT MMQ
UNITARY PACKAGING MEASUREMENT UNIT MMT	UNITS CONTAINED PACKAGING 10	PACKAGING GROSS WEIGHT 0.43
UNITARY PACKAGING VOLUME 1201200	PACKAGING HEIGHT 52	PACKAGING NET WEIGHT 0.43
UNITARY PACKAGING VOLUME UNIT MMQ	PACKAGING WIDTH 105	PACKAGING WEIGHT UNIT KGM