

BNC connector 75 Ohms female with trim plate white Simon K45

REF. K102D/9



BASIC INFORMATION

DESCRIPTION

The BNC 75 Ohms female is part of the series of Simon K45 and is included a trim plate. It has a in a classic colour white that facilitates its integration anywhere in the room of the home, office or premises where it is. Its installation is very simple and can be carried out either by flush mounted or instalándolo directly in surface-mounted. Its dimensions are 22.5 x 45 millimetres. Its type of clamping is by welding and its type of operation is by insertion. Simon advises, bear in mind that the maximum length of cabling recomendaba for this connector if it is wire RG-6, is 90 metres. The connector is manufactured with metal components with self-extinguishing and halogen-free thermoplastic insulation.. This means that contributes to of fire propagation in case of fire and that reduces the toxicity of smoke, which gives much security to the final set.

FINISH

White

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-030)

PACKAGING CONTENTS

BNC 75 Ohms female connector

ETIM CLASS

EC000018

REMARKS

Maximum wire length recommended; 90 metres (RG-6 cable). For additional information, please read the product instruction sheet

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

FORMAT

BNC

RAL

9003

CABLE SECTION ADMITTED (MM)

From 0,2 to 0,5 mm

IP RATING

IP20

STORAGE TEMPERATURE RANGE

(°C)

-25 - 50 °C

CONNECTOR TYPE

BNC

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

VERSION

Single

NUMBER OF CONTACTS

1

NUMBER OF WIRES

2

NUMBER OF POSSIBLE ELEMENTS

1/2 element

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-030)

INSTALLATION TYPE

Suitable for surface and flush mounting

REGULATIONS

REGULATIONS

Dir. 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.015

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING VOLUME

911400

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8426436046924

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

0.3

UNITS CONTAINED PACKAGING

10

PACKAGING GROSS WEIGHT

0.15

UNITARY PACKAGING VOLUME
UNIT

MMQ

PACKAGING HEIGHT

70

PACKAGING NET WEIGHT

0.15

UNITARY PACKAGING GROSS
WEIGHT

0.015

PACKAGING WIDTH

93

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

140