

Duplex fibre optic socket outlet matt black Simon 270

REF. 20000546-098



BASIC INFORMATION

FINISH

Matt black

COMPATIBILITY

Simon 270 frames

ETIM CLASS

EC001409

MATERIAL

Thermoplastic

PACKAGING CONTENTS

Duplex fibre optic connector,
cover and instruction sheet

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

FORMAT

Optical fiber

TYPE OF MECHANISM

Insertion

CABLE SECTION ADMITTED (MM)

From 1,5 to 2,5 mm

IP RATING

IP20

OPERATING TEMPERATURE

RANGE (°C)

5 - 45 °C

CONNECTOR TYPE

Optical fiber

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

RAL

9005

NUMBER OF POSSIBLE ELEMENTS

1 element

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal

INSTALLATION DIRECTION

Horizontal

INSTALLATION TYPE

Suitable for flush mounting

REGULATIONS

REGULATIONS

EN 50173-1:2018

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053266434

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.05

PRODUCT NET WEIGHT

0.05

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053265130

UNITS CONTAINED PACKAGING

5

PACKAGING HEIGHT

55.5

PACKAGING WIDTH

117

PACKAGING LENGTH

280

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

1818180

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

0.25

PACKAGING WEIGHT UNIT

KGM



Para información más detallada consultar la hoja de instrucciones
For more detailed information check the instruction sheet