

2-way switch for card with 2 micro switch and light indicator 250V~ aluminium Simon 75

REF. 75550-33



BASIC INFORMATION

DESCRIPTION

6A and 250V 2-way switch for card with 2 microswitches. It is in aluminium colour and is also available in the following finishes: Graphite, bronze, grey, ivory and white. Type of fast-terminals connection. Supports a section of wire of 0.5 mm This manufactured by metal components with halogen-free insulation and thermoplastic trims. For a proper cleaning of this component, it is recommended to avoid abrasive products containing chlorine and to use a dry and soft cloth. It incorporates a 1mA consumption indicator light and belongs to the range of special control mechanisms of the Simon 75 series. Important considerations when installing: Keep in mind that it is recommended the installation combined with a contactor / relay. If this is not the case, the maximum current of the 2-way switch is 6A (2A inductive). For position, place the frame correctly, the flanges of the same.

FINISH

Aluminium

PACKAGING CONTENTS

Mechanism and cover

COMPATIBILITY

Simon 75 frames

ETIM CLASS

EC001590

REMARKS

A contactor must be installed at the output of the mechanism. If this is not done, the maximum current of the switch is 10 A resistive (1.5 A inductive). It is recommended to protect the faston connectors with a heat shrink sleeve.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

INDICATOR FUNCTION

Yes

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

CABLE SECTION ADMITTED (MM)

0,5 mm

CURRENT (A)

10 (1,5 ind.) A

POWER SUPPLY (V~)

250 V~

CONSUMPTION INDICATOR (mA)

1 mA

IP RATING

IP20

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

NUMBER OF POSSIBLE ELEMENTS

1 element

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

VERSION

Single

FREQUENCY

50 Hz

TYPE OF MECHANISM

Card

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

CLAW

Simon 27

INSTALLATION DIRECTION

Horizontal, Vertical

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Faston

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal

INSTALLATION TYPE

Suitable for surface and flush mounting

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + Directive 2011/65/UE RoHS + + EN 61058:2002 + EN 61058:2002 A2:2008 + EN 61058-2-1:2011

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.078

PACKAGING MEASUREMENT

UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT

UNIT

KGM

PACKAGING VOLUME

3017190

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8421053048603

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

1517738

UNITS CONTAINED PACKAGING

5

PACKAGING GROSS WEIGHT

0.39

UNITARY PACKAGING VOLUME

UNIT

MMQ

PACKAGING HEIGHT

82

PACKAGING NET WEIGHT

0.39

UNITARY PACKAGING GROSS

WEIGHT

0.078

PACKAGING WIDTH

83

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

223