

## Charger 1.5 A 5V DC type A USB port aluminium Simon K45

REF. K126C/8



### BASIC INFORMATION

#### FINISH

Aluminium

#### MATERIAL

Thermoplastic

#### COMPATIBILITY

Simon K45 enclosure for mounting on the wall, floor, ceiling and furniture. Not compatible with Simon 500 Cima enclosures (for this, use ref. 2701097-030 and the S27 to Simon 500 Cima adaptor, ref. 50011088-030)

#### PACKAGING CONTENTS

USB charger, trim cover and installation manual

#### ETIM CLASS

EC002949

## TECHNICAL INFORMATION

|                                                   |                                                                                                                     |                             |
|---------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|-----------------------------|
| AVAILABLE MARKET<br>CE                            | IP RATING<br>IP20                                                                                                   | RECESS DIMENSION (MM)<br>40 |
| CABLE SECTION ADMITTED (MM)<br>From 1,0 to 2,5 mm | MAINTENANCE<br>Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine. | USB CHARACTERISTICS<br>7,5W |
| NUMBER OF CONNECTORS<br>1                         | TYPE OF MECHANISM<br>Insertion                                                                                      | USB CURRENT (A)<br>1,5 A    |
| CONNECTOR TYPE<br>USB A                           | POWER SUPPLY (V~)<br>230 V~                                                                                         | USB VOLTAGE (V~)<br>5 Vdc   |
| NUMBER OF CONTACTS<br>2                           | RAL<br>9006                                                                                                         | VERSION<br>Single           |
| FORMAT<br>USB A                                   |                                                                                                                     | NUMBER OF WIRES<br>2        |

## INSTALLATION AND MAINTENANCE

|                                                                                              |                                                                              |                                                   |
|----------------------------------------------------------------------------------------------|------------------------------------------------------------------------------|---------------------------------------------------|
| CABLE STRIPPING NECESSARY (MM)<br>8                                                          | INSTALLABLE IN FLUSH MOUNT JUNCTION BOX<br>Universal and specific Simon K45. | TYPE OF TERMINAL CONNECTION - FUNCTION 1<br>Screw |
| REMOVAL OF CONNECTOR<br>Only with tool                                                       | INSTALLATION DIRECTION<br>Horizontal, Vertical                               | TYPE OF TERMINAL CONNECTION - FUNCTION 2<br>Screw |
| EXTINGUISHING (°C)<br>+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-10-2) | INSTALLATION TYPE<br>Suitable for surface and flush mounting                 |                                                   |

## REGULATIONS

### REGULATIONS

UNE 20315-1-1:2009 + 20315-1-2:2009 + NF C-61314:2008 + A1:2010

## LOGISTICS INFORMATION

### UNITARY EAN CODE

8421053195055

### UNITARY PACKAGING HEIGHT

0

### UNITARY PACKAGING WIDTH

0

### UNITARY PACKAGING LENGTH

0

### UNITARY PACKAGING VOLUME

0

### UNITARY PACKAGING GROSS WEIGHT

0.045

### PRODUCT NET WEIGHT

0.045

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING EAN

8421053195055

### UNITS CONTAINED PACKAGING

1

### PACKAGING HEIGHT

50

### PACKAGING WIDTH

42

### PACKAGING LENGTH

50

### PACKAGING MEASUREMENT UNIT

MMT

### PACKAGING VOLUME

105000

### PACKAGING VOLUME UNIT

MMQ

### PACKAGING GROSS WEIGHT

0

### PACKAGING NET WEIGHT

0.045

### PACKAGING WEIGHT UNIT

KGM