

PD-24 PIR+LUX recessed KNX white IP20

REF. 89218716-130



BASIC INFORMATION

DESCRIPTION

Presence and brightness detector for flush mounting PIR. The recommended installation height is 2.8 m, with a maximum height of 4 m. It has a detection angle of 360 °. The tangential detection range is 24 m and the radial detection range is 5.5 m.

The brightness regulation range is 2 - 800 lux. The configuration of the detector is done through potentiometers and KNX.

It has a TEACH operating mode. Possibility of interconnection between sensors via KNX. The control protocol is KNX. The typical consumption is 10 mA.

The power supply voltage is KNX (21 - 30 VDC). The operating temperature of the detector is: -20 - 50 °C. White finish, IP 20 protection rating, and dimensions: Ø 109 x 114 mm.

5-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

ETIM CLASS

EC001582

TECHNICAL INFORMATION

IP RATING

IP20

POWER SUPPLY (V~)

Bus KNX (21 Vcc...32 Vcc)

CONTROL

KNX

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

2

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053342992

UNITARY PACKAGING GROSS WEIGHT

0.332

PACKAGING LENGTH

141

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.197

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

2803221

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8421053342992

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

0.332

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

141

PACKAGING NET WEIGHT

0.197

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

141

PACKAGING WEIGHT UNIT

KGM