USB 2.0 connector type A for half element graphite Simon 27 Play

REF. **2701090-038**



BASIC INFORMATION

DESCRIPTION

USB 2.0 type A connector, half element in graphite colour and of the Simon 27 Play series, a range to enjoy decorating your home, taking the initiative to redecorate the spaces in the home, with the interchangeable sleeves and rockers with each other, even you can customize the covers with your favourite images photos. The USB 2.0 connector has an installation with a screw terminal connection, will allow you to connect any wire USB 2.0 increased the speed of load or data exchange, install the cable outlet for a comfort USB 2.0 anywhere in your home, its installation is concerned, it is suitable for surfaces or to be recessed. The element has a maximum recommended length of five metres for slow charging devices and 2.2 metres for fast charging devices. The temperature at which it operates at full capacity is between 5ºC and 40ºC.

FINISH

Graphite

COMPATIBILITY

Simon 27 Play, Simon 27 Neos, Simon 27 Scudo, Simon 27, Simon 27 Centralisations and Simon 44 Aqua frames

PACKAGING CONTENTS

USB female connector and instruction sheet

ETIM CLASS

EC000018

REMARKS

Recommended maximum cable length: 5 metres for low-speed devices and 2.2 metres for high-speed devices. For more information see the product instruction sheet.

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

CABLE SECTION ADMITTED (MM)
From 0,2 to 0,5 mm

NUMBER OF CONNECTORS
1

CONNECTOR TYPE
USB

NUMBER OF CONTACTS
5

NUMBER OF POSSIBLE ELEMENTS
Half element

FORMAT
USB

IP RATING
IP20

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TYPE OF MECHANISM
Insertion

OPERATING TEMPERATURE RANGE (°C)
5 - 40 °C

STORAGE TEMPERATURE RANGE (°C)
-25 - 50 °C

VERSION
Single

NUMBER OF WIRES
5

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)
5

CLAW
Simon 27

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX
Universal, American, Small spaces and Centralisations

INSTALLATION TYPE
Suitable for surface and flush mounting

TYPE OF TERMINAL CONNECTION - FUNCTION 1
Screw

REGULATIONS

REGULATIONS
Directive 2011/65/UE RoHS + EN 50581:2012

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053117682

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
0.055

PRODUCT NET WEIGHT
0.055

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053117682

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
57

PACKAGING WIDTH
76

PACKAGING LENGTH
76

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
329232

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0

PACKAGING NET WEIGHT
0.055

PACKAGING WEIGHT UNIT
KGM