

Optical sensor 10m 110° wall surface IP white IP20

REF. 89243543-330



BASIC INFORMATION

DESCRIPTION

Wall-mounted optical presence and luminosity detector. The recommended installation height is 2.8 m, with a maximum height of 6 m. It has a detection angle of 110° and an opening angle of 110°. The tangential detection range is 10 m and the radial detection range is 10 m. The luminosity regulation range is . The detector configuration is done via IP. Possibility of interconnection between sensors. The control protocol is IP. The power supply voltage is 220 - 240 VAC. The operating temperature of the detector is: 0 - 40 °C. White finish, IP protection grade 20, and dimensions: 180 X 125 X 75 mm. 5-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

ETIM CLASS

EC001582

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

POWER SUPPLY (V~)

220/240 V~

CONTROL

On/Off

IP RATING

IP20

RAL

9010

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

2.3

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053400128

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.39

PRODUCT NET WEIGHT

0.265

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053400128

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

75

PACKAGING WIDTH

125

PACKAGING LENGTH

180

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

2325323

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.39

PACKAGING NET WEIGHT

0.265

PACKAGING WEIGHT UNIT

KGM