Monoblock floor trunking 2.75m and 130x18mm with 3 compartments

REF. **TF21183/8**



BASIC INFORMATION

DESCRIPTION

The monoblock DCS TF21183/8 floor trunking is a robust and secure option for cable distribution indoors, especially in commercial and industrial environments. Made of aluminum with an anodized finish, it has a 130x18 mm profile and offers a high IK08 impact protection rating. Its maximum load capacity is 75 kg/cm^2, making it suitable for areas with constant traffic. The installation system ensures solid fixing on non-combustible floors, and the monoblock design provides greater security by keeping the trunking completely closed and inaccessible once installed, complying with UNE-EN 50085-1 standards.

FINISH	MATERIAL	ETIM CLASS
Aluminium	Aluminium	EC000722

TECHNICAL INFORMATION

IK CLASSIFICATION
08

IP RATING
IP4X

KIT AVAILABILITY
No

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

RAL
7035

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS
Only with tool

REMOVAL OF COVER
Only with tool

REMOVAL OF THE FRAME
Only with tool

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
0

PRODUCT NET WEIGHT
1.345

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436035621

UNITS CONTAINED PACKAGING
11

PACKAGING HEIGHT
150

PACKAGING WIDTH
110

PACKAGING LENGTH
3040

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
50160000

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
1.35

PACKAGING NET WEIGHT
14.795

PACKAGING WEIGHT UNIT
KGM