

## Kit Flash 90 consisting of israelian modular power socket, USB charger Type C 100W (distributed in 65+30W if connected at the same time) and grommet (cable outlet) black Simon K45

REF. KR3530001/14



### BASIC INFORMATION

#### DESCRIPTION

Kit Flash 90 based on a modular israelian power socket-outlet for installation in furniture with an optional protective lid to allow it to be closed and conceal the connections when not in use. Includes a 100W USB Type-C charger (distributed to 65+30W if connected simultaneously) and a cable outlet in black finish. Supplied with a 20cm long cable tie terminated with a 3-pole Wieland® Gst18i male quick-connector with a safety anchor to facilitate safe connection and disconnection from the mains without interrupting the power supply. The kit is supplied assembled with the internal connections pre-made. All that is required is to cut the hole in the furniture where the product will be mounted. Once this is done, connect it to the mains power supply for operation.

#### FINISH

Black

#### MATERIAL

Plastic

#### ETIM CLASS

EC002759

## TECHNICAL INFORMATION

### AVAILABLE MARKET

CE

### CURRENT (A)

16 A

### SNAP-FIT RJ45 PLATES

No

### PROTECTION AGAINST DIRECT ACCESS OF CONTACTS

Yes

### IP RATING

IP20

### SNAP-FIT TYPE

No

### PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS

Protective lid available (as an option) to protect the connections against entry of dust and small objects

### MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### USB CHARACTERISTICS

Charging

### RJ45 CONNECTORS

No

### NOMINAL VOLTAGE (V~)

250 V~

### USB CURRENT (A)

20 A

### CONNECTOR TYPE

Israeli

### RAL

9005

### POWER DELIVERY USB

Yes

### NUMBER OF CONTACTS

3

### RECESS DIMENSION (MM)

ø80 mm

### QUICK CHARGE USB

Yes

### FORMAT

Israeli

### RJ45 ADAPTOR MODULE

No

### USB VOLTAGE (V~)

5 V~

### VOLTAGE (V~)

250 V~

## INSTALLATION AND MAINTENANCE

### REMOVAL OF COMPONENTS

No tools needed

### REMOVAL OF COVER

Only with tool

### EXTINGUISHING (°C)

+650 °C (according to standard IEC 60670)

## REGULATIONS

### REGULATIONS

Dir. 2014/35/UE LVD\*1 | Dir. 2014/30/UE EMC\*3 | Dir. 2011/65/UE RoHS + post. mod.\*1 | Dir. 2009/125/EC ErP (Reg. UE 2019/1782) \*1 \*13 \*12 | S.I. 2016 No. 1101 - The Electrical Equipment (Safety) Regulations 2016\*2 | S.I. 2012 No. 3032 - The Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2012\*2 | IEC 60884-1 Ed.3.2\*1 | BS 1363-2:2016+A1:2018\*2 | UNE 20315-1-1:2017\*5 | BS 1363-4:2016+A1:2018\*2 | UNE 20315-1-2:2017\*5 | DS 60884-2-D1:2023\*4 | CEI 23-50 V4\*7 | SANS 164-1:2021\*6 | SN 441011-2-1:2019\*9 | SI 32 Fig. 204 B\*8 | AS/NZS 3112:2017\*11 | EN 50173-1:2018\*10 | EN 50563:2011 + A1:2013\*13 \*12 | EN 55032:2015 + A11:2020 + A1:2020\*12\*14 \*16 | EN 62368-1: 2014 + A11:2017\*13 \*12 | EN 55035:2017 + A11:2020\*12\*14 \*16 | ETSI-EN 301489-34 V2.1.1\*13 | EN IEC 61000-3-2:2019 + A1:2021 + A2:2024\*12 \*16 | EN IEC 60670-1:2021+ A11:2021\*15 | EN 61000-3-3:2013 +A1:2019 + A2:2021 \*12 \*16 | EN IEC 63000:2018

## LOGISTICS INFORMATION

### UNITARY EAN CODE

8421053398531

### UNITARY PACKAGING HEIGHT

0

### UNITARY PACKAGING WIDTH

0

### UNITARY PACKAGING LENGTH

0

### UNITARY PACKAGING MEASUREMENT UNIT

MMT

### UNITARY PACKAGING VOLUME

0

### UNITARY PACKAGING VOLUME UNIT

MMQ

### UNITARY PACKAGING GROSS WEIGHT

0.65

### PRODUCT NET WEIGHT

0.635

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING EAN

8421053398531

### UNITS CONTAINED PACKAGING

1

### PACKAGING HEIGHT

120

### PACKAGING WIDTH

130

### PACKAGING LENGTH

252

### PACKAGING MEASUREMENT UNIT

MMT

### PACKAGING VOLUME

3931200

### PACKAGING VOLUME UNIT

MMQ

### PACKAGING GROSS WEIGHT

0.796

### PACKAGING NET WEIGHT

0.635

### PACKAGING WEIGHT UNIT

KGM