# Trim plate for tube inlet or cable gland 22 mm diameter for 1 element white Simon K45

REF. **K19/9**



# BASIC INFORMATION

## DESCRIPTION

Trim plate for tube inlet or cable gland 22 millimetres diameter. It is only one element and commitment to a discreet, simple and beautiful finished in white colour, it is part of the series Simon K45. It should be noted that does not include the cable gland, which would have to buy it separately if necessary. If you you'll need to increase the diameter of access, it is possible to extract the pre-punched and increase the diameter to 29 millimetres. This is the individual version of the trim plate, which has half module and no signaling function. It can be installed on surface-mounted or embedded. its dimensions are 45 x 45 millimetres and a depth of 8.5 millimetres. It is manufactured from thermoplastic components, free of halogens, which prevent the propagation of the fire management and whose toxicity in case of smoke, is minimal. Thanks to these materials, the plate can withstand extreme temperatures, ranging from -5 to the + 60 degrees centigrade.

## FINISH

White

## MATERIAL

Plastic

## COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-030)

## PACKAGING CONTENTS

Conduit or cable gland entry plate

## ETIM CLASS

EC000011

## REMARKS

Cable gland is not included (to be purchased separately). If a larger access diameter is required, the pre-punched sections can be removed to increase the diameter to 29 mm.

## TECHNICAL INFORMATION

### AVAILABLE MARKET
CE

### AVAILABLE IN
Versions of plates that provide direct access to the wiring, combination of isolated wiring and 20x30 trunking

### MAX TEMP DURING CONSTRUCTION WORK (°C)
+60° C

### INDICATOR FUNCTION
No

### IP RATING
IP20

### KIT AVAILABILITY
No

### MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 to 60° C

### NUMBER OF MODULES
Half

### RAL
9003

### VERSION
Single

## INSTALLATION AND MAINTENANCE

### TYPE OF FASTENING
Fixing by direct snap-fit, no tools needed

### INSTALLABLE IN FLUSH MOUNT JUNCTION BOX
Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-030)

### INSTALLATION DIRECTION
Vertical according to the direction of the mechanisms

### INSTALLATION TYPE
Suitable for surface and flush mounting

### REMOVAL OF THE PLATE
Only with tool

## REGULATIONS

### REGULATIONS
Directive 2014/35/UE LVD + EN 60670-1:2005

## LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
45570

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.009

PRODUCT NET WEIGHT
0.009

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436036659

UNITS CONTAINED PACKAGING
20

PACKAGING HEIGHT
70

PACKAGING WIDTH
93

PACKAGING LENGTH
140

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
911400

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.18

PACKAGING NET WEIGHT
0.18

PACKAGING WEIGHT UNIT
KGM