

2-way switch for card with 2 micro switch and light indicator 250V~ aluminium Simon 75

REF. 75550-33



BASIC INFORMATION

DESCRIPTION

6A and 250V 2-way switch for card with 2 microswitches. It is in aluminium colour and is also available in the following finishes: Graphite, bronze, grey, ivory and white. Type of fast-terminals connection. Supports a section of wire of 0.5 mm This manufactured by metal components with halogen-free insulation and thermoplastic trims. For a proper cleaning of this component, it is recommended to avoid abrasive products containing chlorine and to use a dry and soft cloth. It incorporates a 1mA consumption indicator light and belongs to the range of special control mechanisms of the Simon 75 series. Important considerations when installing: Keep in mind that it is recommended the installation combined with a contactor / relay. If this is not the case, the maximum current of the 2-way switch is 6A (2A inductive). For position, place the frame correctly, the flanges of the same.

FINISH

Aluminium

COMPATIBILITY

Simon 75 frames

PACKAGING CONTENTS

Mechanism and cover

REMARKS

A contactor must be installed at the output of the mechanism. If this is not done, the maximum current of the switch is 10 A resistive (1.5 A inductive). It is recommended to protect the faston connectors with a heat shrink sleeve.

TECHNICAL INFORMATION

AVAILABLE MARKET CE	INDICATOR FUNCTION Yes	NOMINAL VOLTAGE (V~) 250 V~
CABLE SECTION ADMITTED (MM) 0,5 mm	CURRENT (A) 10 (1,5 ind.) A	OPERATING TEMPERATURE RANGE (°C) 5 - 40 °C
CONSUMPTION INDICATOR (MA) 1 mA	IP RATING IP20	POWER SUPPLY (V~) 250 V~
NUMBER OF POSSIBLE ELEMENTS 1 element	MAINTENANCE Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.	STORAGE TEMPERATURE RANGE (°C) -25 - 50 °C
FREQUENCY 50 Hz	TYPE OF MECHANISM Card	VERSION Single

INSTALLATION AND MAINTENANCE

CLAW Simon 27	INSTALLATION DIRECTION Horizontal, Vertical	TYPE OF TERMINAL CONNECTION - FUNCTION 1 Faston
INSTALLABLE IN FLUSH MOUNT JUNCTION BOX Universal	INSTALLATION TYPE Suitable for surface and flush mounting	

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + Directive 2011/65/UE RoHS + + EN 61058:2002 + EN 61058:2002 A2:2008 + EN 61058-2-1:2011

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
1517738

UNITARY PACKAGING VOLUME
UNIT
MMQ

UNITARY PACKAGING GROSS
WEIGHT
0.078

PRODUCT NET WEIGHT
0.078

UNITARY PACKAGING WEIGHT
UNIT
KGM

PACKAGING EAN
8421053048603

UNITS CONTAINED PACKAGING
5

PACKAGING HEIGHT
82

PACKAGING WIDTH
83

PACKAGING LENGTH
223

PACKAGING MEASUREMENT
UNIT
MMT

PACKAGING VOLUME
3017190

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.39

PACKAGING NET WEIGHT
0.39

PACKAGING WEIGHT UNIT
KGM