

Flat voice and data plate with dust cover for 2 RJ45 BeldenCDT® for 1 element graphite Simon 500 Cima

REF. 50013089-038



BASIC INFORMATION

DESCRIPTION

Model of plate for Voice and data connections number 50004085-033 part of the products and components The professional range Simon 500 Cima, compatible for the assembly of Different types of installations professionals. This is a flat base plate. Voice and data plate with dust cover with 1 element for 2 RJ45 connectors with format Snap-fit BeldenCDT ® RJ45 connectors with the technical quality and appearance of The Simon 500 Cima series. Presents shade in the finishes in graphite, also guarantees The security in situations risk with the flame and smoke thanks to its Metallic components with self-extinguishing thermoplastic insulation. Ease of its fastening In vertical and horizontal enclosures without the need of measures adaptor. 50 x 50 x 11 mm and a depth of 11 mm, being a piece that can be adapted to Different kinds of environments work and in different systems And installations professionals.

FINISH

Graphite

PACKAGING CONTENTS

Flat voice and data plate with
dust cover

ETIM CLASS

EC000018

COMPATIBILITY

Simon 500 Cima enclosures

REMARKS

The plate is snap-fitted for mounting in vertical and horizontal enclosures without the need for an adaptor.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST SHUTTER

Yes

NUMBER OF MODULES

1

AVAILABLE IN

Plate for 1 and 2 RJ45

FORMAT

RJ45

PLATE TYPE

Flat

COMPATIBLE WITH CONNECTORS

BeldenCDT® GigaFlex MDVO.

IP RATING

IP20

RAL

7021

RJ45 CONNECTORS

Not included in voice and data plate

KIT AVAILABILITY

No

RJ45 ADAPTOR MODULE

Included in voice and data plate

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT RJ45 PLATES

BeldenCDT® RJ45 connectors

SNAP-FIT TYPE

BeldenCDT® RJ45 connectors

DUST PROTECTION

Yes

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

VERSION

Single

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Specific Simon 500 Cima

INSTALLATION DIRECTION

Vertical, corresponding with the direction of the mechanisms

INSTALLATION TYPE

Fixing by direct snap-fit, no tools needed.

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053096772

PACKAGING VOLUME

0.604

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

10

PACKAGING VOLUME UNIT

DMQ

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

54

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING GROSS
WEIGHT

0.017

PACKAGING WIDTH

52

PACKAGING NET WEIGHT

0.17

PRODUCT NET WEIGHT

0.017

PACKAGING LENGTH

215

PACKAGING WEIGHT UNIT

KGM

