Kirk Sandall Industrial Estate, Doncaster, South Yorkshire, DN3 1QR

+44 (0)1302 310 113
enquiries@prosolveproducts.com
www. prosolveproducts.com

ProSolve® is a registered trademark of S.T.L Trading Company Limited
Reg in England No: 5230722
VAT Reg No: 381 3533 58

DATA SHEET

ProSolve Prime and Seal (SEAL5)

Product Description & Recommended Use

- A quick-air-drying, penetrating primer-coat which gives a matt finish.
- Made with high-quality alkyd resins and is lead and chrome-free.
- Excellent penetration into concrete and non-ferrous metal substrates.
- Designed to soak into the substrate, providing excellent adhesion of subsequent top coats.
- Will reduce the risk of delamination, due to poor penetration of top-coats, by anchoring the top-coat to the floor.
- Easy to apply by roller or brush.
- The ideal base for ProSolve Floor Paints to give a superior quality finish to your floor.
- Recommended for medium-duty commercial and industrial areas.
- **Note:** Stir well prior to use.

Key Benefits

- Quick-Drying
- Excellent Penetration into Substrate (Reducing Delamination Risk)
- Formulated with High-Quality Synthetic Resins

Dry Film Appearance	Matt
Spreading Rate	5.5-8m2 per litre
Touch Dry @20°C	15-30 minutes
Recoating Time @20°C	14 hours
Typical Wet-Film Thickness	120-160µm per coat
Typical Dry-Film Thickness	65-90µm per coat
Solids by Volume	56% (ASTM D2697) ±3%, dependent on colour
VOC Information	430g per litre
Application Temperature	10-35°C
Application Method	Brush or roller
Substrates	Suitably cleaned and dry surfaces
Thinners	Xylene
Flash Point	≥25°C
Pack Size	5 litre can
Shelf Life	48 months

IMPORTANT NOTICE

All statements, technical information and recommendations are based on tests we believe to be reliable as at the date of hereof, but the accuracy or completeness thereof is not guaranteed. Please ensure before using the product that it is suitable for your intended use. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, other than for fraudulent misrepresentation, ProSolve expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information.

BEFORE USE, CONSULT THE SAFETY DATA SHEET OF THE PRODUCT.