

Technical Specification

CLICK® ScolmoreGROUP

Product Code: VPSC066BK Description: Twin Non-Isolated Coaxial Outlet





Insert: Urea

Earth Plate: Mild Steel

General Information

Plate Dimensions (mm) 88 (W) \times 88 (H) \times 8 (D) Dimensions With Gasket (mm) 91 (W) \times 91 (H) \times 9 (D)

Plate Fixing Centres - Horizontal (mm) 60.3

Style Victorian
Finish Satin Chrome

Insert Colour Black
Gasket Colour Black

Materials Front Plate: Stainless Steel

Terminals: Brass

Gasket: Nylon

Anti Microbial Certified No

Termination Type Screw

Isolated No Non-Isolated Yes

Shielded No

Minimum Back Box Depth (mm) 16

Ingress Protection IP20

Operational Temperature (°C) -5 to +40

Warranty (Years) 10

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. Isolated socket will filter out any interference, if a 2 way signal is required, i.e. for use with satellite hard wire extensions, then a pen independ outlet is required.

wire extensions, then a non-isolated outlet is required.