



CorePro GLASS LED candles and lustres

CorePro LEDCandleND 2-25W E14B35 827CL G

Featuring a classic heritage design, these filament LED candles combine the familiar shapes of classic incandescent bulbs with the benefits of long-lasting LED technology. The LED candle bulb is a very easy choice for people who are looking for a retrofit LED replacement, it provides 90% energy savings compared with conventional lamps. CorePro Glass LED bulbs provide excellent quality of light for stairway lighting. The LED candle bulb offers a lifetime of 15,000 hours to reduce maintenance costs.

Product data

General Information		Photobiological safety according to EN 62471 RG1	
Cap base	E14		
Nominal lifetime	15,000 h		
Switching Cycle	20,000		
Lighting Technology	LED		
Flux measurement reference	Sphere		
Light Technical		Operating and Electrical	
Colour Code	827 [CCT of 2700K]	Line Frequency	50 to 60 Hz
Luminous Flux	250 lm	Input frequency	50 to 60 Hz
Luminous efficacy (rated) (nom.)	125.00 lm/W	Power Consumption	2 W
Colour designation	Warm White (WW)	Lamp current (nom.)	20 mA
Correlated Colour Temperature	2700 K	Wattage equivalent	25 W
Colour consistency	<6	Starting time (nom.)	0.5 s
Colour rendering index (CRI)	80	Warm-up time to 60% light	0.5 s
LLMF at end of nominal lifetime (nom.)	70 %	Power Factor (Fraction)	0.4
Flickering value (PstLM)	1	Voltage (nom.)	220-240 V
Stroboscopic effect	0.4		
		Temperature	
		T-Case maximum (nom.)	36 °C

CorePro GLASS LED candles and lustres

Controls and Dimming

Dimmable	No
----------	----

Mechanical and Housing

Lamp Finish	Clear
Bulb shape	B35

Approval and Application

Energy Efficiency Class	E
Energy-saving product	Yes
Suitable for accent lighting	No
Energy consumption kWh/1,000 hours	2 kWh
EPREL registration number	387351
CE mark	Yes
EU RoHS compliant	Yes
EyeComfort	Yes


Application Conditions

Can it be used in closed luminaires	No
-------------------------------------	----

Product Data



Order product name	CorePro LEDCandleND 2-25W E14B35 827CL G
Full product name	CorePro LEDCandleND 2-25W E14B35 827CL G
Full EOC	871951437757800
Order code	37757800
Material no. (12 NC)	929001238392
Numerator – quantity per pack	1
Net Weight (Piece)	0.014 kg
EAN/UPC – Product/Case	8719514377578
Numerator – packs per outer box	10
EAN/UPC - Case	8719514377585

Dimensional drawing



Product	D	C
CorePro LEDCandleND 2-25W E14B35 827CL G	35 mm	97 mm

Photometric data




Spectral Power Distribution Colour - CorePro LEDCandleND 2-25W E14B35 827CL G

General uniform lighting - CorePro LEDCandleND 2-25W E14B35 827CL G


CorePro GLASS LED candles and lustres

Photometric data




Light Distribution Diagram - CorePro LEDCandleND 2-25W E14B35 827CL G

Lifetime



Life Expectancy Diagram



Lumen Maintenance Diagram - CorePro LEDCandleND 2-25W E14B35 827CL G

