

**Product Code:** SXPF310W**Description:** Instant Plaster Filler Light Weight (C3) Cartridge**Benefits**

- Ultra lightweight
- Non shrinking
- Paintable with water based and synthetic paints
- Sandable after curing
- Easy to apply
- Easy to clean
- Non corrosive towards metals

**Colour** White**Application**

For filling joints and screw holes in plasterboard walls and ceilings.  
For filling and repairing holes and in static joints in concrete, brickwork and plaster.

**Directions Of Use**

Cut the cartridge seal and screw on the nozzle which should be cut to your required size. Using a skeleton gun, apply the filler into the gap or joint ensuring a good solid fill. Smooth off using a putty knife.

**Limitations**

Not suitable for PE, PP, PC, PMMA, PTFE, soft plastics, neoprene and bituminous substrates  
Not suitable for continuous exposure to water  
Not suitable for movement joints

**Paintability**

Can be over-painted 10 - 20 minutes after application, subject to ambient conditions. Painting over with highly filled emulsion paint can cause craze cracking on the paint surface. Due to the variety of paint compositions, we do recoend preliminary tests for compatibility.

**Cleaning**

Tools to be cleaned after use with water. Hands can be cleaned with SX Multi-Purpose Cleaning Wipes and/or water and soap.

**Additional Information**

Shrinkage		<5%
Application Temperature		+5°C to +30°C
Base		Acrylic dispersion
Flow	ISO 7390	<2mm
Density		0,57 g/ml
Frost Resistance During Transportation		Down to -15°C
Skin Formation		5 Minutes @ +23°C/50% RH
Temperature Resistance		-20°C to +75°C

These values are typical properties and may vary +/-3%

**Shelf Life**

In unopened original packaging between + 5°C and + 25°C, shelf life is up to 12 months from production date, stored in a dry place.

**Health & Safety**

Safety data sheet (MSDS) must be read and understood before use of product. These are available on request.

DoC

