

Technical Specification



Product Code: VPAB520BK **Description:** 10A Ingot 3 Pole Fan Isolation Plate Switch





Insert: Urea

Terminal Torque Value (Nm) 0.5

Earth Strap: Mild Steel

Frequency (Hz) 50

General Information

Plate Dimensions (mm) 88 (W) x 88 (H) x 8 (D)

Dimensions With Gasket (mm) 91 (W) x 91 (H) x 9 (D)

Plate Fixing Centres - Horizontal (mm) 60.3

> Style Victorian Finish Antique Brass

Insert Colour Black

Gasket Colour Black

> Materials Front Plate: Stainless Steel

Switch Cover: Stainless Steel Terminals: Brass Contacts: Silver "on-lay" Copper / Brass

Terminal Screws: Steel & Yellow Passivated

Internal Busbars: Formed Pressed Brass

Gasket: Nylon

Anti Microbial Certified No

Rated Voltage (V~) (Ue) 250

Resistive Load Rating (A) 10

Rated Conditional Short-Circuit Current (Iq) 1500A

> Termination Type Screw

Terminal Size (mm) Ø3.5

Terminal Capacity - Solid (mm²) 4 x 1.5 or 2 x 2.5

Modular Rocker Switches No

Triple Pole Switch

Product Marking Isolator, On, Off'

Minimum Back Box Depth (mm) 16

> Ingress Protection IP20

Operational Temperature (°C) -5 to +40

Warranty (Years)

Standards BS EN 60669-2-4

BS EN 60669-1

Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

