



MASTER VALUE LEDspot MV

MASTER LED spot VLE D 3.7-35W GU10 940 36D

Delivering a warm, halogen-like accent beam, the MASTER VALUE is a perfect fit for spot lighting. Thanks to its high CRI, it achieves more natural colours, creating cosy and comfortable ambience for residential and hospitality projects, and emphasising the beauty of merchandise in retail. These LED spots MV GU10 have the familiar look and feel of spot lamps, keeping the classic beauty of glass spots and adding the strong performance of LED technology. The dimming function enables you to create the atmosphere you desire, and it works with broad selection of dimmers. The MASTER VALUE also offers more energy savings than normal LED spots.

Warnings and Safety

- Operating temperature range is between -20° C and 45° C ambient
- Only to apply in dry or damp locations and most of open fixtures with lamp-holders that offer sufficient space (10 mm free air space)
- Not intended for use with emergency light fixtures or exit lights

Product data


General Information			
Cap base	GU10	Luminous intensity (nom.)	500 cd
Nominal lifetime	25,000 h	Luminous efficacy (rated) (nom.)	85.14 lm/W
Switching Cycle	50,000	Colour designation	Cool White (CW)
Lighting Technology	LED	Correlated Colour Temperature	4000 K
Flux measurement reference	Narrow Cone	Colour consistency	<6
		Colour rendering index (CRI)	90
		LLMF at end of nominal lifetime (nom.)	70 %
		Luminous flux in 90° cone (rated)	285 lm
		Flickering value (PstLM)	1
		Stroboscopic effect	0.4

MASTER VALUE LEDspot MV

Photobiological safety according to EN 62471 RG1	
Operating and Electrical	
Line Frequency	50 to 60 Hz
Input frequency	50 to 60 Hz
Power Consumption	3.7 W
Lamp current (nom.)	20 mA
Wattage equivalent	35 W
Starting time (nom.)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.8
Voltage (nom.)	220-240 V
Temperature	
T-Case maximum (nom.)	80 °C
Controls and Dimming	
Dimmable	Only with specific dimmers
Mechanical and Housing	
Bulb shape	PAR16
Approval and Application	
Energy Efficiency Class	F
Suitable for accent lighting	Yes

Energy consumption kWh/1,000 hours	4 kWh
EPREL registration number	391885
CE mark	Yes
EU RoHS compliant	Yes
EyeComfort	Yes
Application Conditions	
Can it be used in closed luminaires	No
Product Data	
Order product name	MAS LED spot VLE D 3.7-35W GU10 940 36D
Full product name	MASTER LED spot VLE D 3.7-35W GU10 940 36D
Full EOC	871869670777700
Order code	70777700
Material no. (12 NC)	929001348402
Numerator – quantity per pack	1
Net Weight (Piece)	0.038 kg
EAN/UPC – Product/Case	8718696707777
Numerator – packs per outer box	10
EAN/UPC - Case	8718696707784



Dimensional drawing



Product	D	C
MAS LED spot VLE D 3.7-35W GU10 940 36D	50 mm	54 mm


MASTER VALUE LEDspot MV

Photometric data





Accent Lighting Spots - MAS LED spot VLE D 3.7-35W GU10 940 36D

Spectral Power Distribution Colour - MAS LED spot VLE D 3.7-35W GU10 940 36D



Light Distribution Diagram - MAS LED spot VLE D 3.7-35W GU10 940 36D

Lifetime



25K LED

Lumen Maintenance Diagram - MAS LED spot VLE D 3.7-35W GU10 940 36D

MASTER VALUE LEDspot MV

