

# Technical Specification

**Product Code:** MD005PW

**Description:** 10AX 1 Way Retractive Switch Module



## General Information

<b>Dimensions (mm)</b>	25 (W) x 53 (H) x 20 (D)	
<b>Finish</b>	Polar White	
<b>Materials</b>	Rocker Switch: Urea Terminals: Brass Contacts: Silver "on-lay" Copper / Brass	Rear Housing: Nylon Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass
<b>Anti Microbial Certified</b>	Yes	
<b>Rated Voltage (V~) (Ue)</b>	250	<b>Frequency (Hz)</b> 50
<b>Inductive Load Rating (AX)</b>	10	
<b>Load Rating Comments</b>	Suitable for Inductive Loads	
<b>Termination Type</b>	Screw	
<b>Terminal Size (mm)</b>	Ø3.5	<b>Terminal Torque Value (Nm)</b> 0.5
<b>Terminal Capacity - Solid (mm²)</b>	4 x 1.5 or 2 x 2.5	
<b>Modular Rocker Switches</b>	Yes	
<b>1 Way Switch</b>	Yes	
<b>Retractive Contact Options</b>	Press to Make	
<b>Product Marking</b>	Bell Symbol	
<b>Minimum Back Box Depth (mm)</b>	16 (25 Flat Plate)	
<b>Operational Temperature (°C)</b>	-5 to +40	
<b>Warranty (Years)</b>	10	

**Additional Information** For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Suitable and matches the Definity, Mode, Polar & Part M ranges