



CorePro LEDspot MV



CoreProLEDspot 4-50W GU10 827 36D DIM UK

CorePro LEDspots are a perfect fit for spot lighting and deliver warm halogen-like light. They are compatible with most existing fixtures with a GU10 or E14 holder and are designed as a retrofit replacement for halogen or incandescent spots. LEDlamps deliver huge energy savings and minimize maintenance cost.

Product data

Cap base	GU10	
Nominal lifetime	15,000 h	
Switching Cycle	50,000	
Lighting Technology	LED	
Light Technical		
Colour Code	827 [CCT of 2700K]	
Beam angle (nom.)	36 degree(s)	
Luminous Flux	345 lm	
Luminous intensity (nom.)	700 cd	
Luminous efficacy (rated) (nom.)	86 lm/W	
Colour designation	Warm White (WW)	
Correlated Colour Temperature	2700 K	
Colour consistency	<6	
Colour rendering index (CRI)	80	
LLMF at end of nominal lifetime (nom.)	70 %	
Luminous flux in 90° cone (rated)	345 lm	
Flickering value (PstLM)	1	
Stroboscopic effect	0.4	
Photobiological safety according to EN 62	471 RG1	

Operating and Electrical	
Line Frequency	50 to 60 Hz
Input frequency	50 to 60 Hz
Power Consumption	4 W
Lamp current (nom.)	23 mA
Wattage equivalent	50 W
Starting time (nom.)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.84
Voltage (nom.)	220-240 V
Temperature	
T-Case maximum (nom.)	70 °C
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Bulb shape	PAR16
Approval and Application	
Energy Efficiency Class	F
Suitable for accent lighting	Yes

Datasheet, 2023, April 15 data subject to change

CorePro LEDspot MV

Energy consumption kWh/1,000 hours	4 kWh
EPREL registration number	400299
EU RoHS compliant	Yes
EyeComfort	Yes
Application Conditions	
Can it be used in closed luminaires	No
Product Data	
Order product name	CoreProLEDspot 4-50W GU10 827 36D
	DIM UK


DIM UK

CoreProLEDspot 4-50W GU10 827 36D

Full EOC	871869672137701
Order code	72137701
Material no. (12 NC)	929002495999
Numerator – quantity per pack	1
Net Weight (Piece)	0.048 kg
EAN/UPC — Product/Case	8718696721377
Numerator – packs per outer box	10
EAN/UPC - Case	8719514406100


Dimensional drawing

Full product name




Product	D	С
CoreProLEDspot 4-50W GU10 827 36D DIM UK	50 mm	54 mm

Photometric data




Light Distribution Diagram - CoreProLEDspot 4-50W GU10 827 36D DIM UK



Spectral Power Distribution Colour - CoreProLEDspot 4-50W GU10 827 36D DIM UK

CorePro LEDspot MV


Photometric data




Cato, LuX Photametricx 4.5 Philips Lighting ScV. Fago: 177

Accent Lighting Spots - CoreProLEDspot 4-50W GU10 827 36D DIM UK

Lifetime





Life Expectancy Diagram

Lumen Maintenance Diagram - CoreProLEDspot 4-50W GU10 827 36D DIM UK



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.