

Technical Specification

Product Code: VPBN426BK

Description: 2 Gang MiniGrid® Unfurnished Plate - 6 In-Line Apertures



General Information

| | | |
|---|---|---|
| Plate Dimensions (mm) | 146 (W) x 88 (H) x 8 (D) | |
| Dimensions With Gasket (mm) | 149 (W) x 91 (H) x 9 (D) | |
| Plate Fixing Centres - Horizontal (mm) | 120.6 | |
| MiniGrid Plate (Gang) | 2 | |
| MiniGrid Single Width Module Quantity | 6 | |
| MiniGrid Double Width Module Quantity | 3 | |
| Style | Victorian | |
| Finish | Black Nickel | |
| Insert Colour | Black | |
| Gasket Colour | Black | |
| Materials | Front Plate: Stainless Steel Terminals: Brass Earth Strap: Mild Steel | Insert: Urea Terminal Screws: Steel & Yellow Passivated Gasket: Nylon |
| Anti Microbial Certified | No | |
| Termination Type | Screw | |
| Modular Rocker Switches | Yes | |
| Minimum Back Box Depth (mm) | Dependent On Modules Fitted | |
| Ingress Protection | IP20 | |
| Operational Temperature (°C) | -5 to +40 | |
| Warranty (Years) | 10 | |

Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. Interchangeable with modules in the MiniGrid Range.

