

# JC71744EM

## Skypack QR Emergency

Skypack QR LED Batten 5ft Twin IP20 4000K 62W 7200Lm Emergency



### Features & Benefits

- Intelligent press release buttons for simple installation
- Ultra efficient up to 114 lumens per circuit Watt
- Suspended LED tray for easy installation
- Press fit terminals loop in loop out
- Rear and end conduit entry points
- Microwave dimmable and on/off options
- 2 years standard warranty extends to 5 years when registered within the first year of purchase (2 years on batteries)(See Website for terms and conditions)



### General Information

Mounting	<b>Surface Mounted</b>
Environment	<b>Indoor</b>
Product Group	<b>LED - Surface</b>
Product Range	<b>Skypack™</b>
Trade Name	<b>Skypack™ QR</b>
Color Finish	<b>White</b>
Product Shape	<b>Rectangular</b>
Product Weight(kg)	<b>2.141</b>
Overall Dimensions	<b>1523 x 70 x 76.5</b>
Light Source	<b>LED</b>
Light Source Features	<b>Neutral White</b>
Recommended Product Location	<b>Domestic, Commercial and Industrial Applications</b>
Method Of Fix	<b>Surface with Conduit Entry</b>
IP Rating	<b>IP20</b>
Origin of manufacturer	<b>Made In China</b>
Warranty	<b>2 years standard warranty extends to 5 years when registered within the first year of purchase (2 years on batteries)(See Website for terms and conditions)</b>
Driver Manufacturer	<b>JCC</b>
LED Manufacturer/Type	<b>XINDA</b>

Lighting Product Type 1

**Linear Lighting**

Lighting Product Type 2

**Emergency Lighting**

## Electrical

Voltage Rating	<b>220-240</b>
Primary Running Current(Amp)	<b>0.35</b>
Operating Frequency Hz	<b>50/60Hz</b>
Secondary running current(mA)	<b>1400</b>
Constant Current or Constant Voltage	<b>CC</b>
Luminaire Circuit Wattage	<b>62</b>
Class	<b>I</b>
EMC Compliant (EN55015)	<b>Yes</b>
Power Factor Correction	<b>0.9</b>
Input Electrical Connections	<b>Switched live, unswitched live, Earth &amp; Neutral</b>
Dimmable	<b>No</b>

## Emergency Data

Load Voltage(DC)	<b>24-54</b>
LOR % in Emergency Mode	<b>8-12</b>
Inverter PFC	<b>0.5</b>

## Battery Data

Battery Specification	<b>6.4V 2000mAH LIFEP04</b>
Battery Type	<b>LIFEP04</b>
Nominal Battery Current	<b>0.35Amp</b>
Charge Current	<b>30-400mA</b>
Recharge Time	<b>12 Hours</b>
Battery Total Weight(kg)	<b>0.05</b>

## Performance Data

LED Life (Hours)	<b>54000</b>
------------------	--------------

Hours life stated is an indication of expected L70 chip and light output calculations when operating in optimum conditions. Product warranty period supports the full product during the term given. The L70 hours expectancy is not correlated with the full product warranty term, nor is it a representation of lumen depreciation during the warranty period.

Energy Rating	<b>This product contains a light source of energy efficiency class F</b>
Actual Lumen Output	<b>7200</b>
Lumens Per Circuit Watt	<b>116</b>
Color Rendering Index	<b>80-89</b>
CRI: Ra	<b>80</b>
Correlated Color Temperature	<b>4000K</b>
Beam Angle °	<b>120</b>
LOR (Light Output Ratio) %	<b>100</b>
Photometry Available	<b>Yes</b>

## Construction

Primary Material

Steel

Outer Diffuser

Polycarbonate

## Packaging

Product Packaged Weight(kg)

2.438

Quantity Per Outer Carton

6

Outer carton(L)- cm

156.5

Outer carton(W)- cm

32

Outer carton(H)- cm

21.5

Outer carton Net weight- kg

12.85

Outer carton Gross weight- kg

15.68

Product Bar Code EAN-13 Number

5052544080524

Outer carton Bar Code ITF-14 Number

15052544080521

## Standards & Approvals

Manufactured In Accordance To

BS EN 60598:2015, 2-1, 2-22

CE Marked

Yes

UKCA Marked

Yes

Date code/Purchase order No.

Yes

WEEE Symbol

Yes

Certificate Of Conformity

Available on request

Accredited Members

LIA, ISO9001-2015, ISO14001-2015



