



Straight Plug IP44

- Designed for ease of assembly and wiring.
- Twist grip cable gland locking system.
- Rated current up to 32A.
- IK08 rating as per IEC/EN 62262.
- Thermoplastic grip material.



PM32/1100FPB

LW MULTIMAX PROTECTED PLUG 2P+E 32A 6H IP44

TECHNICAL DATA		REGISTRY	
Rated current	32A	Net weight	0.19KG
Frequency	50/60Hz	EAN Code	8014950031474
Poles	2P+ $\overline{\text{E}}$	Gross Weight	0.21KG
Protection degree	IP44	Min order quantity	1
Nominal Operating Voltage ²	N/A	REFERENCE STANDARDS STANDARDS	
Clock Position	6h	EN 60309-1:1999	2014/35/EU (LVD)
Rated operating voltage	230V	EN 60309-2:1999/A1:2007	2012/19/EU (WEEE)
Manufacturing material	Thermoplastic	EN 60309-1:1999/A1:2007	2011/65/EU (RoHS)
		EN 60309-2:1999	
		EN 60309-2:1999/A2:2012	
		EN 63000:2018	
		EN 50581:2012	
		EN 60309-1:1999/A2:2012	
		EN 60309-1:1999/A1AC:2014	