RCD In-line - 30mA Active

The PowerBreaker J62 provides added personal protection against electrocution when using electrical equipment. The units have double pole protection and are re-wire-able. For use in adverse conditions, such as building sites, plant applications, industrial manufacturing, where water presents a danger and rough handling is expected. Also trips on loss of power supply, preventing unexpected start up of equipment.


Suitable for BS/European power supply systems

Robust construction

Double pole breaking

Mechanical flag to indicate contact position

Separate 'Test' and 'Reset' buttons









Tel: 01279 772 772 Fax: 01279 422 007

Email: sales@greenbrook.co.uk www.greenbrook.co.uk



-Power-Breaker-

The PowerBreaker J63-X is a two pole in-line portable RCD for indoor use only. It has built in IEC connectors for easy fit, and quick release from the appliance. Ideal for use in commercial and office environments.

The incoming end of the in-line RCD has the built in IEC connector in the housing, and must be connected to the mains supply. The outgoing supply has a 0.3 metre length of cable, which is fitted with an IEC plug.

		I	1	
	J62-T	J62-Y	J63-X	
Product Finish	Orange	Yellow	Black	
Barcode	5012739606441	5012739606458	5012739607783	
Product Weight	232g		203g	
Product Dimensions	H 161.50 x W 50.80 x D 47mm		47mm	
Voltage	240V AC ~ 50/60Hz	110V AC ~ 50/60Hz	240V AC ~ 50/60Hz	
Max Operating Current	16A		10A (3A inductive load)	
IP Rating	IP65 Note: To ensure the IP rating, terminals & cover should be sealed with the supplied sealant (2 x 14ml tubes).		IP20 (indoor use only)	
Cable Type		e Flexible Cable - 11.7mm)	IEC Connector in housing	
Rated Trip Current	30mA			
Typical Trip Speed	<40mS		<40mS	
RCD Contact Break	Double Pole			
Latching	Active - Electrical, needs resetting after Power Loss			
		Polycarbonate		
Main Housing Material		Polycarbonate		
Main Housing Material Guarantee		Polycarbonate 1 Year		