

Product Code: CL835

Description: 13A 1 Gang Double Pole Switched Socket Outlet With Neon



General Information

Dimensions (mm)	80 (W) x 80 (H) x 42 (D)		
Plate Fixing Centres - Horizontal (mm)	60.3		
Style	Metal Clad		
Finish	Metal Clad Grey		
Materials	Front Plate & Mounting Box: Electrophoretically Coated Steel	Insert:	Urea
	Rear Housing: Urea	Neon Lens:	Polycarbonate
	Terminals: Brass	Terminal Screws:	Steel & Yellow Passivated
	Contacts: Silver "on-lay" Copper / Brass	Internal Busbars:	Formed Pressed Brass
	Earth Strap: Mild Steel		
Rated Voltage (V~) (Ue)	250	Frequency (Hz)	50
Resistive Load Rating (A)	13		
Termination Type	Screw	Terminal Torque Value (Nm)	2
Terminal Size (mm)	Ø5		
Terminal Capacity - Solid (mm²)	3 x 2.5 or 2 x 4		
Double Pole Switch	Yes	Indicator Colour	Red
Neon Indicator	Yes		
Supplied Back Box Depth (mm)	40	Back Box Knockouts - Sides (mm)	1 x Ø20
Back Box Knockouts - Total (mm)	5 x Ø20	Back Box Knockouts - Rear (mm)	None
Back Box Knockouts - Top (mm)	2 x Ø20		
Back Box Knockouts - Bottom (mm)	1 x Ø20		
Back Box Earth Terminal Supplied	Yes		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	10		

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
 Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
 Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.