


Technical Specification



Product Code: VPBN504BK Description: 45A Ingot 2 Gang Double Pole Switch With 13A Double Pole Switched

Socket Outle





Insert & Rear Housing: Urea

Frequency (Hz) 50

Gasket: Nylon

Terminal Torque Value (Nm) 2.5

Terminal Screws: Steel & Yellow Passivated

Internal Busbars: Formed Pressed Brass

General Information

Plate Dimensions (mm) 146 (W) \times 88 (H) \times 8 (D) Dimensions With Gasket (mm) 149 (W) \times 91 (H) \times 9 (D)

Plate Fixing Centres - Horizontal (mm) 120.6

Style Victorian
Finish Black Nickel
Insert Colour Black
Gasket Colour Black

Materials Front Plate: Stainless Steel

Terminals: Brass Contacts: Silver "on-lay" Copper / Brass

Earth Strap: Mild Steel

Anti Microbial Certified No

Rated Voltage (V~) (Ue) 250

Resistive Load Rating (A) 45
Termination Type Screw

Terminal Size (mm) ∅6

Terminal Capacity - Solid (mm²) 1 x 16

Double Pole Switch Yes

Twin Earth Terminals Yes

Product Marking On, Off, Socket, Cooker

Minimum Back Box Depth (mm) 35

Ingress Protection IP20

Operational Temperature (°C) -5 to +40

Warranty (Years) 10

Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

