

---

## P RF CLAS GL 60 6 W/827 E27

PARATHOM Retrofit CLASSIC GLOBE | LED lamps, classic ball shape



---

### Areas of application

- Domestic applications
- General illumination
- Outdoor applications only in suitable luminaires
- Perfect for decorative installations

---

### Product benefits

- Clear lamps with innovative LED "filament" technology
- Very low energy consumption
- Instant 100 % light, no warm-up time
- Can be easily fitted instead of ordinary light bulbs

---

### Product features

- Professional LED lamps for line voltage
- Not dimmable
- Mercury-free lamps
- Lifetime: up to 15,000 h
- Beam angle: up to 360°
- Energy efficiency class: A++



# Product datasheet

## Technical data

### Electrical data

|  |             |
|--|-------------|
| Rated wattage                          | 6.00 W      |
| Nominal wattage                        | 6.00 W      |
| Nominal voltage                        | 220...240 V |
| Operating frequency                    | 50...60 Hz  |
| Power factor $\lambda$                 | > 0.50      |
| Claimed equiv. conventional lamp power | 60 W        |


### Photometrical data

|                                      |                           |
|--------------------------------------|---------------------------|
| Nominal luminous flux                | 806 lm                    |
| Rated luminous flux                  | 806 lm                    |
| Color temperature                    | 2700 K                    |
| Color rendering index Ra             | $\geq 80$                 |
| Light color (designation)            | Warm White                |
| Standard deviation of color matching | $\leq 6$ sdc <sub>m</sub> |

### Light technical data

|                     |          |
|---------------------|----------|
| Warm-up time (60 %) | < 0.50 s |
| Starting time       | < 0.5 s  |

### Dimensions & weight



|                |          |
|----------------|----------|
| Overall length | 168.0 mm |
| Diameter       | 124.0 mm |
| Outer bulb     | G125     |
| Length         | 168.0 mm |

### Lifespan

## Product datasheet

|  |         |
|--|---------|
| Nominal lamp life time                   | 15000 h |
| Rated lamp life time                     | 15000 h |
| Number of switching cycles               | 100000  |
| Lumen main.fact.at end of nom.life time  | 0.70    |
| Lumen maintenance at end of service life | 0.70    |

### Additional product data

|                                   |        |
|-----------------------------------|--------|
| Base (standard designation)       | E27    |
| Mercury content                   | 0.0 mg |
| Mercury-free                      | Yes    |
| Design / version                  | Clear  |
| Appropriate disposal acc. to WEEE | Yes    |

### Capabilities

|          |    |
|----------|----|
| Dimmable | No |
|----------|----|

### Certificates & standards

|                         |             |
|-------------------------|-------------|
| Energy efficiency class | A++         |
| Energy consumption      | 6 kWh/1000h |

### Country specific categorizations

|                 |                              |
|-----------------|------------------------------|
| ILCOS           | DRAG/C-6/827-220-240-E27-124 |
| Order reference | PRFCLG125606W/8              |

### Logistical Data

| Product code  | Product description         | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Volume                | Gross weight |
|---------------|-----------------------------|------------------------------|--------------------------------------|-----------------------|--------------|
| 4052899972773 | P RF CLAS GL 60 6 W/827 E27 | Shipping carton box<br>10    | 710 mm x 290 mm x<br>366 mm          | 75.36 dm <sup>3</sup> | 1616.00 g    |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.