




**Product Description:** Slim-Fit<sup>™</sup> 18W IP44 Round Low Profile Downlight


The range of Slim-Fit<sup>™</sup> low profile downlights are engineered to deliver superior light output and uniformity utilising the latest edge-lit LED technology. At only 20mm deep including bracket, they are an ideal solution where ceiling voids are limited but high lumen output is required.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour	SKU Type
EN-PL18C/30	18	3000	1710	95	120	Matt White	Non Dimmable
EN-PL18C/40	18	4000	1890	105	120	Matt White	Non Dimmable
EN-PL18C/65	18	6500	1800	100	120	Matt White	Non Dimmable
EN-PL18CDA/30	18	3000	1710	95	120	Matt White	DALI Dimmable
EN-PL18CDA/40	18	4000	1890	105	120	Matt White	DALI Dimmable
EN-PL18CDA/65	18	6500	1800	100	120	Matt White	DALI Dimmable
EN-PL18CV/30	18	3000	1710	95	120	Matt White	1-10V Dimmable
EN-PL18CV/40	18	4000	1890	105	120	Matt White	1-10V Dimmable
EN-PL18CV/65	18	6500	1800	100	120	Matt White	1-10V Dimmable


## Line Drawing



## Polar Curve



## Colour



Matt White

## Feature & Benefits

- Low cost energy savings compared to compact fluorescents
- Edge-lit low profile ideal for installations with limited recess space (25mm) and shallow ceiling voids
- Plug & play remote driver supplied (40mm space required)
- Separate triac dimmable driver available
- Life not affected by frequent switching e.g. when used with occupancy controls
- IP44
- TP(a) rated
- 1.5kV surge protected
- L70 B50 40000hrs
- 5 year warranty
- 3 year onsite warranty (registration required) \*Terms and conditions apply

## Product Specs:

Input Voltage	220~240V AC
Power Factor	0.9
Lifetime L70 (hrs)	40000hrs
Lamp Base	None
Weight (Kg)	0.421
Product Type	Downlights
Operating Temp. (Min) °C	-10°C

Input Frequency	50/60HZ
IP Rating	IP44
IK Rating	IK04
Overall Diameter (mm)	225
Height (mm)	20
Cutout Diameter (mm)	206-206
Operating Temp. (Max) °C	40°C

## Compliance & Approvals:



## Warranty:

---

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.