



Ledinaire floodlights gen3

BVP164 LED77/830 PSU 70W SWB CE

830 warm white - Symmetrical

This Ledinaire floodlights range contains a selection of popular off-the-shelf LED luminaires that comes with the Philips high quality levels at a competitive price. Reliable, energy-efficient and affordable – just what you need.

Product data

General information		Number of products on MCB (16 A type B)	
Lamp family code	-	31	
Light source colour	830 warm white	Photobiological risk	Photobiological risk group 1 @ 200mm to EN62471
Light source replaceable	No	Photobiological risk specification	0.2 m
Number of gear units	1 unit	EU RoHS compliant	Yes
Driver/power unit/transformer	No [-]	Light source engine type	LED
Driver included	Yes		
Optical cover/lens type	G [Glass]	Light technical	
Luminaire light beam spread	110° x 110°	Upward light output ratio	0
Control interface	-	Standard tilt angle post-top	-
Connection	Flying leads/cables	Standard tilt angle side entry	-
Cable	Cable 2.0 m without plug (C2K)		
Protection class IEC	Safety class I	Operating and electrical	
Flammability mark	NO [-]	Input Voltage	220 to 240 V
CE mark	CE mark	Input frequency	50 or 60 Hz
ENEC mark	-	Initial CLO power consumption	- W
Warranty period	3 years	Average CLO power consumption	70 W
Optic type outdoor	Symmetrical	End CLO power consumption	- W
Constant light output	No	Inrush current	3.64 A

Ledinaire floodlights gen3

Inrush time	0.0222 ms
Power factor (min.)	0.95

Controls and dimming

Dimmable	No
----------	----

Mechanical and housing

Housing material	Aluminium die-cast
Reflector material	Polycarbonate
Optic material	Glass
Optical cover/lens material	Tempered glass
Fixation material	Steel
Mounting device	MBA [Mounting bracket adjustable]
Optical cover/lens shape	Flat
Optical cover/lens finish	Clear
Overall length	203 mm
Overall width	284 mm
Overall height	27 mm
Effective projected area	0.038 m ²
Colour	Grey
Dimensions (height x width x depth)	27 x 284 x 203 mm (1.1 x 11.2 x 8 in)

Approval and application

Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK07 [2 J reinforced]
Surge protection (common/differential)	4/4 kV
Sustainability rating	-

Initial performance (IEC compliant)

Initial luminous flux (system flux)	7700 lm
Luminous flux tolerance	+/-10%

Initial LED luminaire efficacy	110 lm/W
Init. Corr. Colour Temperature	3000 K
Init. Colour rendering index	>80
Initial chromaticity	(0.440, 0.403) SDCM <5
Initial input power	70 W
Power consumption tolerance	+/-10%
Init. colour rendering index tolerance	+/-2

Over time performance (IEC compliant)

Control gear failure rate at median useful life 50,000 h	5 %
Lumen maintenance at median useful life* 50,000 h	80

Application conditions


Ambient temperature range	-25 to +40 °C
Performance ambient temperature Tq	25 °C
Maximum dimming level	Not applicable

Product data

Full product code	871951453360899
Order product name	BVP164 LED77/830 PSU 70W SWB CE
EAN/UPC – product	8719514533608
Order code	53360899
SAP numerator – quantity per pack	1
Numerator – packs per outer box	10
SAP material	911401845483
Net Weight (Piece)	1.350 kg



Dimensional drawing



BVP164 LED77/830 PSU 70W SWB CE

Ledinaire floodlights gen3

