

Technical Specification



Product Code: CMA145PL Description: 1 Gang Unfurnished Dimmer Plate & Knob (650W Max) - 1 Aperture



General Information

Plate Dimensions (mm) 86 (W) x 86 (H) x 9.5 (D)

Plate Fixing Centres - Horizontal (mm) 60.3

> Style Rounded Profile Finish Polar White

Materials Front Plate & Control Button: Urea

> Terminal Screws: Steel & Yellow Passivated Earth Strap: Mild Steel

Yes

Anti Microbial Certified Termination Type

Screw

Minimum Back Box Depth (mm) 25 Ingress Protection IP20

Operational Temperature (°C) -5 to +40

Warranty (Years)

Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.

Terminals: Brass

All products have been independently tested with 99.9% of enveloped viruses and 92% of nonenveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of

bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.

MD9014: 100W Dual Mode LED Dimmer Module **Compatible Dimmer Modules**

MD9001: 6A Push ON/OFF (Dummy Dimmer / Non Dimmable) Module

MD9010: 1-10V Analogue Rotary Dimmer Module MD9022: 40-250W Leading Edge Dimmer Module MD9042: 60-400W Leading Edge Dimmer Module



