

Technical Specification



Product Code: MD024BN

Description: 20A Ingot 2 Way Switch Module





Dimensions (mm)	41 (W) x 52.5 (H) x 22 (D)	
Finish	Black Nickel	
Materials	Rocker Switch: Urea	Rear Housing: Nylon
	Switch Cover: Stainless Steel	Terminals: Brass
	Terminal Screws: Steel & Yellow Passivated	Contacts: Silver "on-lay" Copper / Brass
	Internal Busbars: Formed Pressed Brass	
Rated Voltage (V~) (Ue)	250	Frequency (Hz) 50
Resistive Load Rating (A)	20	
Termination Type	Screw	
Terminal Size (mm)	Ø4.4 Terminal	Torque Value (Nm) 1.2
Terminal Capacity - Solid (mm ²)	3 x 2.5 or 2 x 4	
Modular Rocker Switches	Yes	
2 Way Switch	Yes	
Minimum Back Box Depth (mm)	25 (35 Flat Plate)	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	10	
Ensure th	eaning / polishing of products, use only a soft, dry, clean cloth. e that the mains supply is isolated before commencing installation and refer to the circuit am with the relevant product.	

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tarnworth, Staffordshire, B79 7UL United Kingdom T: +44 (0)1827 63454 | F: +44 (0)1827 63362 E: sales@scolmore.com | W: scolmore.com



Page 1 of 1 (19/02/22) Errors & Omissions excluded. Specification is subject to change without notice.