

Technical Specification



Product Code: WA222

Description: 60A Junction Box 3 Terminal



General Information

Dimensions (mm) 153 (W) × 91 (D) × 35 (H) Finish Brown Materials Body: Urea Earth Terminals: Brass Terminal Screws: Steel and Yellow Passivated Anti Microbial Certified Yes Rated Voltage (V~) (Ue) 250 Frequency (Hz) 50 Resistive Load Rating (A) 60 60 Cable Restraint Entry Size (mm) 30 x 11 50 Terminal Size (mm) Ø7.6 Terminal Torque Value (Nm) 2.5 Terminal Capacity - Solid (mm?) 1 x 25 50 Entry Knockout Dimensions (mm) 23 x 20 (30 x 20 Full) (x2) 50 Operational Temperature (°C) -20 to +55 Varranty (Years) 10 Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.				
Materials Body: Urea Terminal Screws: Steel and Yellow Passivated Anti Microbial Certified Yes Rated Voltage (V~) (Ue) 250 Prequency (Hz) 50 Resistive Load Rating (A) 60 Cable Restraint Entry Size (mm) 30 x 11 Terminal Capacity - Solid (mm) 07.6 Terminal Capacity - Solid (mm) 1 x 25 Entry Knockout Dimensions (mm) 63 x 20 (30 x 20 Full) (x2) Cable Restraint Entry Size (mm) 23 x 20 (30 x 20 Full) (x2) Cable Restraint Supplie Yes Ingress Protection IP20 Operational Temperature (°C) -20 to +55 Warranty (Years) 10	Dimensions (mm)	153 (W) x 91 (D) x 35 (H)		
Anti Microbial Certified Yes Rated Voltage (V~) (Ue) 250 Frequency (Hz) 50 Resistive Load Rating (A) 60 50 Frequency (Hz) 50 Cable Restraint Entry Size (mm) 30 × 11 50 50 Terminal Size (mm) Ø7.6 Terminal Torque Value (Nm) 2.5 Terminal Capacity - Solid (mm) 1 × 25 50 Entry Knockout Dimensions (mm) 23 × 20 (30 × 20 Full) (x2) 50 Cable Restraint Supplied Yes 50 Ingress Protection IP20 20 to +55 50 Warranty (Years) 10 10 Additional Information For clearuit polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.	Finish	Brown		
Rated Voltage (V~) (Ue) 250 Frequency (Hz) 50 Resistive Load Rating (A) 60 60 60 Cable Restraint Entry Size (mm) 30 × 11 7 7 Terminal Size (mm) Ø7.6 7 7 Terminal Capacity - Solid (mm²) 1 × 25 7 7 Entry Knockout Dimensions (mm) 23 × 20 (30 × 20 Full) (x2) 7 7 Cable Restraint Supplied Yes 7 7 7 Ingress Protection IP20 7 7 7 Operational Temperature (°C) -20 to +55 20 to +55 7 7 Marranty (Years) 10 7 7 7 Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.	Materials	Terminal Screws: Steel and Yellow	Earth Terminals: Bra	SS
Resistive Load Rating (A) 60 Cable Restraint Entry Size (mm) 30 x 11 Termination Type Screw Terminal Size (mm) Ø7.6 Terminal Capacity - Solid (mm²) 1 x 25 Entry Knockout Dimensions (mm) 23 x 20 (30 x 20 Full) (x2) Cable Restraint Supplied Yes Ingress Protection IP20 Operational Temperature (°C) -20 to +55 Warranty (Years) 10 Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.	Anti Microbial Certified	Yes		
Cable Restraint Entry Size (mm) 30 × 11 Termination Type Screw Terminal Size (mm) Ø7.6 Terminal Capacity - Solid (mm²) 1 × 25 Entry Knockout Dimensions (mm) 23 × 20 (30 × 20 Full) (x2) Cable Restraint Supplied Yes Ingress Protection IP20 Operational Temperature (°C) -20 to +55 Warranty (Years) 10 Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.	Rated Voltage (V~) (Ue)	250	Frequency (Hz)	50
Termination Type Screw Terminal Size (mm) Ø7.6 Terminal Torque Value (Nm) 2.5 Terminal Capacity - Solid (mm²) 1 x 25 Terminal Capacity - Solid (mm²) 23 x 20 (30 x 20 Full) (x2) Cable Restraint Supplied Yes Ingress Protection IP20 Operational Temperature (°C) -20 to +55 Warranty (Years) 10 Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.	Resistive Load Rating (A)	60		
Terminal Size (m) Ø7.6 Terminal Torque Value (Nm) 2.5 Terminal Capacity - Solid (mm²) 1 x 25 1 x 25 Entry Knockout Dimensions (mm) 23 x 20 (30 x 20 Full) (x2) 23 x 20 (30 x 20 Full) (x2) Cable Restraint Supplied Yes Ingress Protection IP20 Operational Temperature (°C) -20 to +55 Warranty (Years) 10 Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.	Cable Restraint Entry Size (mm)	30 x 11		
Terminal Capacity - Solid (mm²) 1 x 25 Entry Knockout Dimensions (mm) 23 x 20 (30 x 20 Full) (x2) Cable Restraint Supplied Yes Ingress Protection IP20 Operational Temperature (°C) -20 to +55 Warranty (Years) 10 Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.	Termination Type	Screw		
Entry Knockout Dimensions (mm) 23 x 20 (30 x 20 Full) (x2) Cable Restraint Supplied Yes Ingress Protection IP20 Operational Temperature (°C) -20 to +55 Warranty (Years) 10 Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.	Terminal Size (mm)	Ø7.6	Terminal Torque Value (Nm)	2.5
Cable Restraint Supplied Yes Ingress Protection IP20 Operational Temperature (°C) -20 to +55 Warranty (Years) 10 Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.	Terminal Capacity - Solid (mm ²)	1 x 25		
Ingress Protection IP20 Operational Temperature (°C) -20 to +55 Warranty (Years) 10 Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.	Entry Knockout Dimensions (mm)	23 x 20 (30 x 20 Full) (x2)		
Operational Temperature (°C) -20 to +55 Warranty (Years) 10 Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.	Cable Restraint Supplied	Yes		
Warranty (Years) 10 Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.	Ingress Protection	IP20		
Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.	Operational Temperature (°C)	-20 to +55		
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.	Warranty (Years)	10		
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal	Ensure t diagram	that the mains supply is isolated before commencing installation and refer to the circuit with the relevant product.		
	Bare ea	rth caples must always be covered wi	in appropriate sieeving and wire	a to the earth terminal.