

JC17071

Rechargeable Table Lamps

Round rechargeable lamp with power bank 2W IP54 3000K 154lm White



Features & Benefits

- Ideal for domestic applications, no electrician required
- This portable touch dimmable lamp allows for flexible illumination
- 6 hrs charge time, with up to 12 hrs run time at 100% light output
- Provides a convenient option to charge your phone with the internal USB power bank with up to 7 hrs phone charging time(6 hrs light and phone charging combined)
- Uses Lithium-ion batteries, increased charge and discharge cycles, for longer life span
- 3000K colour temperature to match the Architectural Exterior Range
- IP54 rating, suitable for exterior use



BEAM



CLASS II



CLASS III



CRI:RA



DIMMABLE



RATING



WARRANTY

General Information

Product Group	Architectural Exterior
Product Range	Rechargeable
IK Rating	IP54
Color Finish	White
Product Shape	Conical
Overall Dimensions	291 x 125 Ø
Light Source	LED
Light Source Features	Warm White
Additional Information	UK USB Plug Adapter/ 1.2m USB charging lead.
Origin of manufacturer	China
Warranty	2 years standard warranty extends to 3 years when registered within the first year of purchase (2 years on batteries) (See Website for terms and conditions)
LED Manufacturer/Type	Philips 3014

Electrical

Voltage Rating	220-240V~
Operating Frequency Hz	50/60Hz
Luminaire Circuit Wattage	2
Class	Class II Plug Adapter, Class III luminaire

Battery Data

Battery Specification	2 * 18650 3.7V 2200mAh Lithium-ion
Battery Type	Lithium ion
Nominal Battery Current	4.4 Amp
Charge Current	1 Amp
Recharge Time	(Mains USB) 6 hrs
Battery run time	Running time(Light @Full Power) 12hrs. Phone Charging time only(use as Power Bank only) 7.5 hrs. Light and Phone charging combined -running time 6 hrs

Performance Data

LED Life (Hours)	36000
------------------	--------------

Hours life stated is an indication of expected L70 chip and light output calculations whenoperating in optimum conditions. Product warranty period supports the full productduring the term given. The L70 hours expectancy is not correlated with the full productwarranty term, nor is it a representation of lumen depreciation during the warrantyperiod.

Energy Rating	This product contains a light source of energy efficiency class F
Actual Lumen Output	154
Lumens Per Circuit Watt	77
Standard Deviation Colour Matching - SDCM	>5
Color Rendering Index	80-89
CRI: Ra	84
Correlated Color Temperature	3000K
LOR (Light Output Ratio) %	100
Photometry Available	Yes

Construction

Primary Material	Aluminium
Lens	Clear PC
Heat Sink	Aluminium
Seal Material	Silicon

Packaging

Quantity Per Outer Carton	8
Outer carton(L)- cm	46.5
Outer carton(W)- cm	31.5
Outer carton(H)- cm	36.5
Outer carton Net weight- kg	4.80kg
Outer carton Gross weight- kg	7.40kg
Product Bar Code EAN-13 Number	5052544109423
Outer carton Bar Code ITF-14 Number	15052544109420

Standards & Approvals

Manufactured In Accordance To	BS EN 60598-2015
-------------------------------	-------------------------

CE Marked
UKCA Marked
Date code/Purchase order No.
WEEE Symbol
Certificate Of Conformity
Accredited Members

Yes
Yes
Yes
Yes
Yes, available on request
LIA, ISO9001:2015, ISO14001:2015



